Main key HS marking on the back side 29 ± 0.5 23 ± 0.2 В 4-03.3 ± 0.2 23 ± 0.2 29 ± 0.5 ϕ 20. 5 $^{+0.5}_{-0.3}$ $(\phi 16.6)$ С С (φ 14) 10.5 \pm 0. 1 6 23 ± 0.5 3 ± 0.3 4 D D 5 2 ϕ 19.9 $^{+0.4}_{-0.2}$ Solder pot dia(ϕ 1.7) Ε Ε PHENOL FORMALDEHYDE (BLACK) UL94V-0 3 PHENOL FORMALDEHYDE (BLACK) UL94V-0 STAINLESS STEEL 2 NICKEL PLATING COPPER ALLOY 6 STEEL SILVER PLATING 2μm min ALUMINUM ALLOY 5 NICKEL PLATING 1 FINISH NICKEL PLATED PHOSPHOR BRONZE NO. MATERIAL REMARKS ΝO MATERIAL REVISIONS DESIGNED CHECKED DATE SCALE COUNT DESCRIPTION OF UNITS 15. 09. 14 DRAWING APPROVED : HY. KOBAYASHI EDC-119156-00-00 HIROSE ELECTRIC CHECKED : HY. KOBAYASHI 15.09.14 PART JRC16BR-7SA DESIGNED : KN. IKEHARA 15.09.14 CODE NO. CL114-0305-0-00 15. 09. 14 DRAWN ·KN. IKEHARA FORM HC0011-5-51

Dec.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hirose Electric: JRC16BR-7SA