



ASF22RG



Active

## Slide Switches



[Always ELV Compliant](#) ([Find RoHS Compliant Alternates/Statement of Compliance](#))

### Product Highlights:

- Number of Positions = 2
- Double Pole - Double Throw Configuration (Pole-Throw)
- Actuator Style = Flush, Side
- Actuator Color = White
- ASE/F Series

[View all Features](#) | [Find Similar Products](#)

[Previous](#) [1](#) [2](#) [3](#) | [4](#) [5](#) ... [20](#) [Next](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- [SLIDE SWITCH ASE/ASE AUTO-INSERTABLE, THRU-HOLE AND...](#) (PDF, English)

### Catalog Pages/Data Sheets:

- [ALCOWITCH PRODUCTS](#) (PDF, English)

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- [Number of Positions](#) = 2
- Configuration (Pole-Throw) = Double Pole - Double Throw
- Actuator Style = Flush, Side
- Mount Angle = Right Angle
- Grade = Telecom
- Termination Type = PC
- Comment = Open Ended (Unsealed) Case

### Electrical Characteristics:

- Contact Rating = 0.4VA

### Body Related Features:

- Actuator Color = White
- Series = ASE/F
- Mount Style = Through-Hole
- Switch Style = Auto-insertable
- PCB Tail Length (mm [in]) = 4.06 [0.160]
- Actuator Material = Polyester

### Contact Related Features:

- Contact Plating = Gold
- Contact Material = Copper Alloy

### Configuration Related Features:

- Terminal Configuration = Standard
- Number of Actuators = Single

### Industry Standards:

- [RoHS/ELV Compliance](#) = ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Always was ELV compliant

### Identification Marking:

- Stamped Marking = With

### Other:

- Brand = Alcoswitch