

### SOLUTIONS PRODUCTS DESIGN SUPPORT BUY & SAMPLE ABOUT CYPRESS

TO A CVECADASATS MAADT

### CY8C4245AZS-M443T 🔣 🚱

Status: In Production





Product Specs	Pricing & Inventory	Packaging/Ordering	Quality and RoHS	Technical Documents
CY8C4245AZS-M443T				DESIGN SUPPORT
Automotive Qualified	Y			
CPU Core	ARM Cortex-MC	1		Development Kits
CapSense	Y			Forums
Dedicated ADC (#Max Resolution @ Rate)	SAR (1, 12-bit @	1 msps)		Knowledge Base
EEPROM (KB)	0			Packaging
Flash (KB)	32			Product Brochures
JTAG and Si ID	0x11E0			Quality & Reliability
LCD Direct Drive	Y			Samples
Max. Operating Frequency (MHz)	48			Technical Support
Max. Operating Temp. (°C)	105			Technical Training
Max. Operating Voltage (V)	5.50			-
Min. Operating Temp. (°C)	-40			Third Party Network (CYPros)
Min. Operating Voltage (V)	1.71			
No. of CAN Controllers	0			
No. of Continuous Time Blocks	1			TRAINING
No. of DMA Channels	8			
No. of Dedicated Comparators	2			Workshops
No. of Dedicated Timer/Counter/P	WM Blocks 8			Training On-Demand
No. of GPIOs	38			Webinars
No. of Op Amps	2			
No. of SIO	0			
No. of Serial Communication Block	s 4			
No. of USB IO	0			
No. of Universal Analog Blocks	0			
No. of Universal Digital Blocks	4			
PLL	N			
SRAM (KB)	4			
Series	PSoC 4200M			
Tape & Reel	Y			
USB (Type)	None			

PRICING & INVENTORY AVAILABILITY						
1-9 unit Price*	10-24 uni Price*	t 25-99 unit Price*	100-249 unit Price*	250-999 un Price*	it 1000+ un Price*	it
		Cor	ntact Sales			

Availability	Quantity	Ships In	Buy from Cypress	Buy from Distributors
Out of Stock	0	Please click here to check lead times	Contact Sales	Contact Sales

\* Prices are shown in United States dollars and are for budgetary use only for volume of 1ku

PACKAGING/ORDERING	
Package	TQFP
No. of Pins	44
Package Dimensions	275 L x 1.4 H x 275 W (Mils)
Package Cross Section Drawing	Download
Package Carrier	REEL
Standard Pack Quantity	1500
Minimum Order Quantity (MOQ)	1500
Order Increment	1500
Estimated Lead Time (days)	91
HTS Code	8542.31.0001
ECCN	(A.3)
ECCN Suball	3A991

QUALITY AND ROHS		
Moisture Sensitivity Level (MSL)	3	
Peak Reflow Temp. (°C)	260 (Cypress Reflow Profile)	
RoHS Compliant	Y Print RoHS Certificate of Compliance	
PB Free	Y	
Lead/Ball Finish	Ni/Pd/Au	
Marking	Cypress Marking Format	
Device Qualification Reports		

TITMTBF, ESD (HBM/CDM) and Latch-up data available in the Device Qualification Report.

QTP#162707-AUTOMOTIVE PSoC 4100M and PSoC 4200M DEVICE FAMILY SBPFHD-10P, FAB25 (AL BEOL INTERCONNECT).pdf Lost Update: Mar 06, 2019

## TECHNICAL DOCUMENTS

### Application Notes (17)

ANABBASE - PSoc Clark Programming Using an External Microcontroller (PHSSP) Jan 19, 2020
ANABBASE - PSoc Clark Programming Using an External Microcontroller (PHSSP) Jan 19, 2020
ANABBASE - PSoc Clark Spock A and PSoc Sch

SOLUTIONS

Industrial

Microcontrollers (MCUs) Universal Serial Bus (USB)

Touch Sensing Clocks & Buffers

PRODUCTS

DESIGN SUPPORT

Community Videos Product Roadmaps ABOUT US

Careers

CORPORATE HEADQUARTERS
Cypress Semiconductor Corp.
198 Champion Court
San Jose, CA 95134 USA
Tel: +1-408-943-2600

CUSTOMER SERVICE SUPPORT +1-800-541-4736 Hours: 8:00AM - 5:00PM (local time) Create a MyCase Cypress Developer Community

INTERNATIONAL SUPPORT +1-408-943-2600 United States +1-800-541-4736 Hours: 4:30AM - 1:30PM (pacific time) 7:30PM - 4:30AM (standard time)

### OTHER REQUESTS

Contact Us
Report a Website Problem
Report a Security Vulnerability

ABOUT US CAREERS INVESTORS LEGAL





# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cypress Semiconductor: CY8C4245AZS-M443T