

COVER 8 WAY

APTIV P/N

13543538

CODING

CODING - A

(1.3)

13567784

CODING - B

2.5 ± 0.1

1.25 ± 0.1

13567785

CODING - C

3.8 ± 0.1

2.5 ± 0.1

13579226

CODING - D

1.75 ± 0.1

1.3 ± 0.1

(11.35)

11

7

13

12

8

9

DELPHI

PBT-GF20

XX

X

14.5

17.25 ± 0.1

SPC 0.55 ± 0.1

11.35 ± 0.1

12.35 ± 0.1

10 ± 0.1

3.6

18.4 ± 0.2

13.5 ± 0.1

11.2 ± 0.1

1 ± 0.1

12.15 ± 0.1

7.15 ± 0.1

3.81 ± 0.12

9.25 ± 0.1

1.75 ± 0.1

1.27

2.54

SPC 8.55 ± 0.1

2.54

1.73

11.3 ± 0.1

8X Ø 0.1 A B C

3X 2.54 = (7.62)

1.3 ± 0.1

B

C

NOTE

SPECIFICATIONS

1

FEMALE CONNECTOR ACCORDING TO APTIV SPECIFICATION: CAQE TBD

2

FEMALE CONNECTOR ACCORDING TO:
-TEMPERATURE CLASS TX
-ENGINE VIBRATOR CLASS VX
-SEALING CLASS EX

3

USER'S MANUAL: 13590051-CUS76-S01

4

DELIVERY CONNECTOR WEIGHT : SEE TABLE

5

NO WAFER HINGE OR WAFER HINGE BROKEN ALLOWED

6

VISUAL DEFECTS ON NO FUNCTIONNAL AREAS ALLOWED

2

MATERIAL NAME

4

TOOL CAVITY NUMBER

4

INDEX REPLCEMENT INSERT

4

PART CAVITY NUMBER

4

SUPPLIER LOGO

4

REPLACMRNT INSERT BLANK

4

DATE INSERT

○ DIM TO CHECK

FROM TO

1 | DIM FOR HELP

□ THEORETIC DIM

DIMENSIONAL RANGE (MM)

> 0

> 20

> 30

> 70

> 100

> 150

> 200

> 250

> 300

> 400

CHART E1

TOLERANCE UNLESS OTHERWISE SPECIFIED

ANGULAR TOLERANCE ±2°

LINE DRAWN THROUGH A PART NUMBER INDICATES THAT PHYSICAL PARTS ARE NOT AVAILABLE FOR ORDERING.

PART NUMBERS THAT DO NOT HAVE A LINE PRESENT INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT APTIV SALES TO ASSURE AVAILABILITY OF PARTS.

SHARP CORNER TOLERANCE

R 0.2 MAX

R 0.1 MAX

DWG. TYP

CUSTOMER PART DRAWING

WEIGHT (GR)

SEE CHART

VOLUME (CM³)

ROUTING

DISTR CODE

D

UNLESS OTHERWISE SPECIFIED

GENERAL TOLERANCES ACCORDING TO:

SEE CHART

GD&T ACCORDING TO:

ISO 1101

REFERENCE

FIRST ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

DR

P.BALAJI

APVD1

LAGUETTE MAURICE

APVD2

LAGUETTE MAURICE

APVD3

APVD4

APVD5

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER APTIV 10949001

MATERIAL

SEE CHART

DRAWING NAME

COVER 8 WAY FOR MQS 0.63

DRAWING NUMBER

13543539

SIZE

A1

SCALE

5:1

FRAME NO

1 OF 1

SHEET NO

1 OF 1

STG

R

REV

01

N/P

ASSOCIATED PARTS (FOR INFORMATION)

DESCRIPTION

APTIV P/N

MATING PART

13590051

INSERT 8 WAY FOR MQS 0.63

15493343

COVER 8 WAY

D

13579226

0.0011

PBT GF20

VIOLET

C

13567785

0.0011

PBT GF20

BLUE

B

13567784

0.0011

PBT GF20

NATURE

A

13543538

0.0011

PBT GF20

BLACK

DESCRIPTION

CODE

APTIV PART NUMBER

WEIGHT (kg)

MATERIAL

COLOR

COVER 8 WAY

APTIV P/N

13543538

CODING

CODING - A

(1.3)

13567784

CODING - B

2.5 ± 0.1

1.25 ± 0.1

13567785

CODING - C

3.8 ± 0.1

2.5 ± 0.1

13579226

CODING - D

1.75 ± 0.1

1.3 ± 0.1

(11.35)

11

7

13

12

8

9

DELPHI

PBT-GF20

XX

X

14.5

17.25 ± 0.1

SPC 0.55 ± 0.1

11.35 ± 0.1

12.35 ± 0.1

10 ± 0.1

3.6

18.4 ± 0.2

13.5 ± 0.1

11.2 ± 0.1

1 ± 0.1

12.15 ± 0.1

7.15 ± 0.1

3.81 ± 0.12

9.25 ± 0.1

1.75 ± 0.1

1.27

2.54

SPC 8.55 ± 0.1

2.54

1.73

11.3 ± 0.1

8X Ø 0.1 A B C

3X 2.54 = (7.62)

1.3 ± 0.1

B

C

NOTE

SPECIFICATIONS

1

FEMALE CONNECTOR ACCORDING TO APTIV SPECIFICATION: CAQE TBD

2

FEMALE CONNECTOR ACCORDING TO:
-TEMPERATURE CLASS TX
-ENGINE VIBRATOR CLASS VX
-SEALING CLASS EX

3

USER'S MANUAL: 13590051-CUS76-S01

4

DELIVERY CONNECTOR WEIGHT : SEE TABLE

5

NO WAFER HINGE OR WAFER HINGE BROKEN ALLOWED

6

VISUAL DEFECTS ON NO FUNCTIONNAL AREAS ALLOWED

2

MATERIAL NAME

4

TOOL CAVITY NUMBER

4

INDEX REPLCEMENT INSERT

4

PART CAVITY NUMBER

4

SUPPLIER LOGO

4

REPLACMRNT INSERT BLANK

4

DATE INSERT

○ DIM TO CHECK

FROM TO

1 | DIM FOR HELP

□ THEORETIC DIM

DIMENSIONAL RANGE (MM)

> 0

> 20

> 30

> 70

> 100

> 150

> 200

> 250

> 300

> 400

CHART E1

TOLERANCE UNLESS OTHERWISE SPECIFIED

ANGULAR TOLERANCE ±2°

LINE DRAWN THROUGH A PART NUMBER INDICATES THAT PHYSICAL PARTS ARE NOT AVAILABLE FOR ORDERING.

PART NUMBERS THAT DO NOT HAVE A LINE PRESENT INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT APTIV SALES TO ASSURE AVAILABILITY OF PARTS.

SHARP CORNER TOLERANCE

R 0.2 MAX

R 0.1 MAX

DWG. TYP

CUSTOMER PART DRAWING

WEIGHT (GR)

SEE CHART

VOLUME (CM³)

ROUTING

DISTR CODE

D

UNLESS OTHERWISE SPECIFIED

GENERAL TOLERANCES ACCORDING TO:

SEE CHART

GD&T ACCORDING TO:

ISO 1101

REFERENCE

FIRST ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

DR

P.BALAJI

APVD1

LAGUETTE MAURICE

APVD2

LAGUETTE MAURICE

APVD3

APVD4

APVD5

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER APTIV 10949001

MATERIAL

SEE CHART

DRAWING NAME

COVER 8 WAY FOR MQS 0.63

DRAWING NUMBER

13543539

SIZE

A1

SCALE

5:1

FRAME NO

1 OF 1

SHEET NO

1 OF 1

STG

R

REV

01

N/P

ASSOCIATED PARTS (FOR INFORMATION)

DESCRIPTION

APTIV P/N

MATING PART

13590051

INSERT 8 WAY FOR MQS 0.63

15493343

COVER 8 WAY

D

13579226

0.0011

PBT GF20

VIOLET

C

13567785

0.0011

PBT GF20

BLUE

B

13567784

0.0011

PBT GF20

NATURE

A

13543538

0.0011

PBT GF20

BLACK

DESCRIPTION

CODE

APTIV PART NUMBER

WEIGHT (kg)

MATERIAL

COLOR

CONTROLLED DOCUMENTS ARE ONLY AVAILABLE ON THE SERVER
User: K259139-cus02-s01/01 Date: 25-Feb-22 Time: 11:15:47
K259139-cus02-s01/01 Date: 25-Feb-22 Time: 11:15:47

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Aptiv:](#)

[13567785](#)