


PART NO. AND CH. CODE	$\Delta W_1 \pm 0.4$	$\Delta W_2 \pm 0.4$	H ₁	H ₂	X	A	B
7116-5044-02 (7B16-5044-02)	2.30	5.20	(2.19)	(4.21)	0.50	12.50	3.00
7116-5045-02 (7B16-5045-02)	3.00	5.30	(2.91)	(4.08)	0.80	12.50	3.00
7116-5046-02 (7B16-5046-02)	4.20	6.00	(4.06)	(5.09)	1.00	13.00	2.00

注記

1. かん合オス端子品番：7114-4025 ETC.
2. ()内品番は、エアバック(A/B)回路及び特別管理回路に使用する時に適用すること。
3. 取扱説明書No.：YPES-15-221
4. 本製品の性能は、JASO D616:2011版(分類2)を満足すること。

NOTES

1. MATING MALE TERMINAL PART NO. : 7114-4025 ETC.
2. PART NUMBERS IN PARENTHESIS SHALL BE USED FOR AIR BAG (A/B) CIRCUITS AND OTHER CIRCUITS DESIGNATED FOR SPECIAL MONITORING.
3. HANDLING MANUAL NO. : YPES-15-221
4. THE PERFORMANCE OF THIS PRODUCT MUST BE IN ACCORDANCE WITH JASO D616:2011th EDITION (CLASSIFICATION 2).



13/08/26		ADDED NOTES, ETC.	C13-Z319	A. Q	CUSTOMER		MATL. SPEC.		COPPER ALLOY (t=0.25)		TREAT. & FIN.		TIN PLATING	
06/09/29		ADDED TOLERANCE	C06-ZA72	T. 0	CUSTOMER PART NO.		CUSTOMER DWG NO.							
05/05/30		NEW	C05-Z852	T. 0	OFFICE		TRIAL PART NO.							
LET	DATE	REVISION RECORD	NO.	CHKD	VENDOR		VENDOR NO.							
GENERAL TOLERANCE														
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO.
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30°	0.1	R	NEW	05/05/30	mm	5:1	3	7116-5044-02 ETC. (7B16-5044-02 ETC.)
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN		DWG NO.
C	±0.3	±0.5	±0.8	±1.4	±2	±30°	0.15	M. FUKUDA	S. SUZUKI	K. KIDA	T. OSADA	A. QUIROL		7116-5044-02:R
SPECIFIED					MASS	g		13/08/26	13/08/26	13/08/26	05/02/08	13/08/26		SET DWG NO.
														YAZAKI CORPORATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Yazaki:](#)

[7116504402](#) [7116504502](#)