SET DWG NO. CIRCUITS AND OTHER CIRCUITS DESIGNATED FOR SPECIAL MONITORING. ()内の品番はA/B回路及び特別管理回路に使用すること。 ISSUE MARK 4. PART NUMBERS IN PARENTHESIS SHALL BE USED FOR AIR/BAG(A/B) 7196-0805-02 (7B96-0805-02) 7289-6868-30 (7089-6868-30)  $\triangle$  7172–5540–80 (7B72–5540–80) SEAL 2. APPLICABLE HOUSING : 7289-6868-30 (7C89-6868-30) 🗥 3. APPLICABLE TERMINAL: 7196-0805-02 (7B96-0805-02) YAZAKI CORPORATION SEALED WIRE & FIN TREAT CIVUS 0.35sq 7172-5540-80:R 1. APPLICABLE WIRE SIZE: CIVUS 0.35sq SILICONE RUBBER (BROWN) △ 2. 適用ハウジング品番: ⚠ 3. 適用ターミナル品番: 2P က 適用電線サイズ: 1.2 A/B PART NO. CH. CODE DWG NO. 川 MATL. SPEC. NAME ♠ SCL ANGLE 2:1 3 2018/06/06 NOTES D. MAI DRAWN  $\triangleleft$  $\triangleleft$ 2016/12/14 R. OHFUKU CUSTOMER DWG NO E E DESIGN LINI TRIAL PART NO. Ф3.90 DWG DATE 2017/02/01 ^ S CHECKED 2018/06/06 DWG SOURCE NEW R. OHFUKU CHECKED CUSTOMER PART NO. 10.30 T. MATSUNAGA 2018/06/06 VENDOR NO DWG TYPE R **APPROVED** CUSTOMER OFF I CE VENDOR D. M A. Q CHKD 0.45 (0.1 ECCENT 0.1 0.1 C18-Y104 C17-Z024 | 10MAX | 50MAX | 120MAX | 250MAX | 2500YR | ANGLE | 10. 15 | 10. 2 | 10.3 | 10.5 | 10.75 | 130 | 10.2 | 10.3 | 10.55 | 10.95 | 11.4 | 130 | 130 | 10.3 | 10.5 | 10.8 | 11.4 | 12 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 130 | MASS 9 ADDED A/B NO., ETC. REVISION RECORD ±2.5 ±3.0 ±5.0 ±6.0 ±0.4 ±0.5 ±0.6 ±1.0 ±0.8  $\pm 2.0$ ±1.5 ±4.0 GENERAL TOLERANCE GENERAL TOLERANCE ±0.6 ±0.8 ±1.0 ±2.5 ±3.0 ±3.5 ±0.5 ±1.4 ±1.6 ±2.0 103 ±1.2 0.6 +1.8  $\pm 0.4$ % ±1.2 ±1.5 ±0.7 ±0.8 ±1.0 ±0.2 ±0.3 ±0.3 ±0.4 ±0.5 PART 2018/06/06 2017/02/01 DATE RUBBER 180 TO 250 250 T0 315 315 T0 400 400 T0 500 10 T0 18 SPECIFIED 0VER 010 E **⋖**|മ|억 A

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Yazaki:

7172554080