



Features

- Partition set is adjustable for different size parts. Fits into the 37750, 37760 and 37762 Tek Trays
- Impregnated corrugated material; greater durability than coated or printed material
- Static dissipative surface resistance of 1 x 10^6 to < 1 x 10^9 ohms per ANSI/ESD STM11.11
- Made from 100% recycled material, and is 100% recyclable
- Reusable, ensuring best value

Cell Height	Cell Length	Cell Width	# of Long Partitions	# of Short Partitions	Cell Total
1-1/2"	2-11/16"	2-1/8"	3	7	32
1-1/2"	2-11/16"	4-3/8"	3	3	16
1-1/2"	2-11/16"	6-5/8"	3	2	8
1-1/2"	2-11/16"	8-7/8"	3	1	8
1-1/2"	5-9/16"	2-1/8"	1	7	16
1-1/2"	5-9/16"	4-3/8"	1	3	8
1-1/2"	5-9/16"	6-5/8"	1	2	4
1-1/2"	5-9/16"	8-7/8"	1	1	4

Meets the required limits of ANSI/ESD S20.20, and Packaging standard ANSI/ESD S541.

SPECIFICATIONS

Properties Typical Values

 1×10^6 to $< 1 \times 10^9$ ohms Surface Resistance

Discharge Shielding < 50 nanoJoules

Tolerances are +/- 10% unless otherwise specified

Negligible surface damage at 10 cycles and <5% of surface **Sloughing Test**

damage at 200 cycles in Taber Abrasion Test. No conductive particles abraded from surface

Recyclability Complete recyclability of package

Test Procedures/Method

ANSI/ESD STM11.11 ANSI/ESD STM 11.31

ASTM D4060 at 70 rpm with CS-17 abrasive-coated

wheels and 1000 grams load

Rockwell International Test Report of January 8, 1992 Rockwell International Test Report of January 8, 1992



Specifications and procedures subject to change without notice.

TEK-TRAY PARTITION SET

BURIED SHIELDING LAYER

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578

ProtektivePak.com

DRAWING NUMBER 37764

DATE: October 2019

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Protektive Pak:

37764