

337 CARD EDGE CONNECTOR

10. WITHDRAWAL FORCE: 1oz MINIMUM PER CONTACT 9. INSERTION FORCE: 16oz MAX. PER CONTACT WHEN

TESTED WITH A .0700" THICK GAUGE.

WHEN TESTED WITH A .0620" THICK GAUGE.

8. OPERATING TEMPERATURE: -65°C TO +125°C 7. INSULATION RESISTANCE: 5000 MEGOHMS MINIMUM

AT SEA LEVEL, BETWEEN ADJACENT CONTACTS.

YOUR CONNECTION TO QUALITY & SERVICE TORONTO, ONTARIO **EDAC INC** CANADA

OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS SHALL NOT BE REPRODUCED, OR COPIED THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND WITHOUT WRITTEN PERMISSION.

> ACAD REFERENCE NO. 337-044-521-300

COMPLIANT

2011/65/EU FOR RoHS COMPLIANCY.

DRAWN: R.STA.MONICA | DATE: OCT.03/2014

PART NUMBER

337-044-521-300

DRAWING NUMBER 337-044-521-300

ISSUE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EDAC:

337-044-521-300