


POS. 2      POS. 3  
POS. 1

POS. 1      POS. 3

( ) = MOMENTARY

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.4VA @20 (AC or DC)
5. FIXED TERM. & MOVING CONTACT:

- 
- Technical drawing of a 1.27 X connector. The drawing includes a top view and a side view. The top view shows a central square area labeled "E-LOGO ON OTHER SIDE" and three pins labeled "1", "2", and "3". The side view shows a cylindrical body with a threaded section labeled "-32 NS THD." and an "EPOXY SEAL" at the base. Dimensions include 4.70 for the pin spacing and 15.75 for the overall width. The connector is labeled "1.27 X" at the bottom.



<b>E-SWITCH®</b>				
TITLE				
100 SP-1 T7 B13 VS3 R EH (GOLD CONTACTS)				
SCALE	DATE	DR	DWG	REV
2:1	11/1/05	PH	ST110011	A

**E-SWITCH®**

100 SP-1 T7 B13 VS3 R EH (GOLD CONTACTS)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[E-Switch:](#)

[100SP1T7B13VS3REH](#)