



Base unit (BU30-MS3) For ET 200SP motor starter With infeed 24 V

product brand name	SIMATIC
product category	Accessories
product designation	BaseUnit
design of the product	For DC feed in
product type designation	ET 200SP
<b>General technical data</b>	
insulation voltage rated value	500 V
degree of pollution	2
surge voltage resistance rated value	6 kV
maximum permissible voltage for protective separation <ul style="list-style-type: none"> <li>• between main and auxiliary circuit</li> </ul>	500 V
shock resistance	6g / 11 ms
vibration resistance	15 mm to 6 Hz; 2g to 500 Hz
reference code according to IEC 81346-2	Q
Substance Prohibitance (Date)	04/15/2016
<b>Safety related data</b>	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe
<b>Main circuit</b>	
number of poles for main current circuit	3
type of voltage of the operating voltage	AC
operating voltage rated value	500 V
operational current at AC at 400 V rated value	32 A; Derating, see Manual
<b>Inputs/ Outputs</b>	
number of digital inputs	0
<b>Supply voltage</b>	
type of voltage of the supply voltage	DC
supply voltage 1 at DC rated value <ul style="list-style-type: none"> <li>• minimum permissible</li> <li>• maximum permissible</li> </ul>	24 V 20.4 V 28.8 V
supply voltage of DC supply	24 V
ampacity maximum	7 A
<b>Installation/ mounting/ dimensions</b>	
mounting position	vertical, horizontal
fastening method	DIN rail
height	215 mm
width	30 mm
depth	75 mm
required spacing with side-by-side mounting <ul style="list-style-type: none"> <li>• upwards</li> </ul>	50 mm

• downwards	50 mm
<b>Ambient conditions</b>	
installation altitude at height above sea level maximum	4 000 m; For derating see manual
<b>ambient temperature</b>	
• during operation	-25 ... +60 °C; For derating see manual
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
environmental category during operation according to IEC 60721	3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices)
relative humidity during operation	10 ... 95 %
air pressure according to SN 31205	900 ... 1 060 hPa

<b>Connections/ Terminals</b>	
<b>type of electrical connection</b>	
• for main current circuit	spring-loaded terminals (push-in)
• for auxiliary and control circuit	spring-loaded terminals (push-in)
<b>type of connecting terminal</b>	Push-in terminal
<b>type of connectable conductor cross-sections at the inputs for supply voltage</b>	
• solid	1x 0.5 ... 2.5 mm <sup>2</sup>
• finely stranded without core end processing	1x 0,5 ... 2,5 mm <sup>2</sup>
• finely stranded with core end processing	1x 0.5 ... 2.5 mm <sup>2</sup>
<b>type of connectable conductor cross-sections</b>	
• at the inputs for supply voltage for AWG cables solid	1x 20 ... 12
<b>type of connectable conductor cross-sections for load-side outgoing feeder</b>	
• solid	1x 0,5 ... 2,5 mm <sup>2</sup>
• finely stranded without core end processing	1x 0,5 ... 2,5 mm <sup>2</sup>
• finely stranded with core end processing	1x 0,5 ... 2,5 mm <sup>2</sup>
<b>type of connectable conductor cross-sections for AWG cables for load-side outgoing feeder</b>	1x 20 ... 12
<b>shape of the screwdriver tip</b>	Slot
<b>size of the screwdriver tip</b>	Standard screwdriver 0.6 mm x 3.5 mm

<b>Certificates/ approvals</b>	
General Product Approval	EMC
	Declaration of Conformity



[Confirmation](#)



Declaration of Conformity	Test Certificates	Marine / Shipping
---------------------------	-------------------	-------------------



[Type Test Certificates/Test Report](#)



other
-------

[Confirmation](#)

**Further information**

Siemens has decided to exit the Russian market (see here).  
<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1908-0AP00-0BP0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1908-0AP00-0BP0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1908-0AP00-0BP0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RK1908-0AP00-0BP0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1908-0AP00-0BP0&lang=en)





last modified:

11/21/2022 

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

[3RK19080AP000BP0](#)