

Xelity 6TX Unmanaged Switch 6 Port 100Mbit

Art.No.: 58811 Weight: 0.139 Country of origin: DE

Model designation: Xelity 6TX

6 port unmanaged switch

Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration





Product may differ from Image







Commercial data		
ECLASS-6.0	19170106	
ECLASS-6.1	19170106	
ECLASS-7.0	19170106	
ECLASS-8.0	19170106	
ECLASS-9.0	19170402	
ECLASS-10.1	19170402	
ECLASS-11.1	19170402	
ECLASS-12.0	19170402	
ETIM-5.0	EC000734	
customs tariff number	85176200	
customs tariff number	85176200	
GTIN	4048879798396	
GTIN	4048879798396	
Packaging unit	1	
Packaging unit	1	
Electrical data Supply		
Operating voltage DC min.	9,5 V	
Operating voltage DC max.	31,5 V	
Industrial communication		
Data transmission rate max.	100 MBit/s	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2025-02-23



stay connected

Diagnostics Alarm contact Diagnostic ED display Device protection Electrical Degree of protection (EN IEC 60529) Dever voltage protection	yes Full duplex unmanaged yes no No voltage Ethernet connection/data traffic IP20 yes
duplex Switch type VLAN unmanaged (IEEE 802.1Q) Diagnostics Alarm contact Diagnostic LED display Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	Full duplex unmanaged yes no No voltage Ethernet connection/data traffic
Switch type VLAN unmanaged (IEEE 802.1Q) Diagnostics Alarm contact Diagnostic LED display Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	unmanaged yes no No voltage Ethernet connection/data traffic
VLAN unmanaged (IEEE 802.1Q) Diagnostics Alarm contact Diagnostic LED display Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	yes no No voltage Ethernet connection/data traffic
Diagnostics Alarm contact Diagnostic LED display Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	No voltage Ethernet connection/data traffic IP20
Alarm contact Diagnostic LED display Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	No voltage Ethernet connection/data traffic IP20
Diagnostic LED display Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	No voltage Ethernet connection/data traffic IP20
Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	Ethernet connection/data traffic IP20
Device protection Electrical Degree of protection (EN IEC 60529) Invers-polarity protection Over voltage protection	IP20
Degree of protection (EN IEC 60529) nvers-polarity protection Over voltage protection	
nvers-polarity protection Over voltage protection	
Over voltage protection	yes
Manager and a second se	yes
Mechanical data Material data	
Color housing	black
Material housing	Plastic
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, (EN 60715)
Height	140 mm
Width	30 mm
Depth	85,1 mm
Environmental characteristics Climatic	
•	05.00
Operating temperature min.	-25 °C 60 °C
Operating temperature max.	-40 °C
Storage temperature min. Storage temperature max.	85 °C
	65 C
Connection type 2	
Connection type 1	6
Family construction form	RJ45
Gender	female
Color contact carrier	black
No. of poles	8
PIN 1	TD+
PIN 2	TD -
PIN 3	RD +
PIN 4	n.c.
PIN 5	n.c.
PIN 6	RD -
PIN 7	n.c.
PIN 8	n.c.
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	4
PIN 1	24 V DC (UB 1)
PIN 2	0 V
PIN 3	PE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murrelektronik:

58811