

MKS - D 20/1300-1 P DIODE MODULES

Mounting rail / screw-type terminal


Art.No.: 67057 Weight: 0.104 Country of origin: CZ Model designation: MKS - D 20/1300-1 P

Universal diode 1 300 V, 1 A 20 diodes Common potential cathode Diode modules are suitable for the suppression of inductive loads (valve, contactor, etc.)

Link to Product







Product may differ from Image



Commercial data

ECLASS-6.0	27371010	
ECLASS-6.1	27371010	
ECLASS-7.0	27371010	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-12-16

Murrelektronik GmbH | Grabenstraße 29 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



ECLASS-8.0	27371010
ECLASS-9.0	27371010
ECLASS-10.1	27371010
ECLASS-11.1	27371010
ECLASS-12.0	27371010
ETIM-5.0	EC002780
customs tariff number	85411000
GTIN	4048879041911
Packaging unit	1
Electrical data Supply	
Operating voltage AC max.	48 V
Operating voltage DC max.	48 V
Installation	
Connection cross section max.	4 mm ²
Installation Connection	
Connection	Screw terminals SK
Connection Mechanical data Mounting data	Screw terminals SK
	Screw terminals SK geschnappt
Mechanical data Mounting data	
Mechanical data Mounting data Mounting method	geschnappt
Mechanical data Mounting data Mounting method Suitable for mounting type	geschnappt Mounting rail TH35, G32, (EN 60715)
Mechanical data Mounting data Mounting method Suitable for mounting type Height	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width Depth	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width Depth Environmental characteristics Climatic	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm 62 mm
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width Depth Environmental characteristics Climatic Operating temperature min.	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm 62 mm -20 °C
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width Depth Environmental characteristics Climatic Operating temperature min. Operating temperature max.	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm 62 mm -20 °C
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width Depth Environmental characteristics Climatic Operating temperature min. Operating temperature max. Connection type 1	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm 62 mm -20 °C 60 °C
Mechanical data Mounting data Mounting method Suitable for mounting type Height Width Depth Environmental characteristics Climatic Operating temperature min. Operating temperature max. Connection type 1 Connection	geschnappt Mounting rail TH35, G32, (EN 60715) 86 mm 45 mm 62 mm -20 °C 60 °C Screw terminals SK

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-12-16

Murrelektronik GmbH | Grabenstraße 29 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murrelektronik:

67057