AMPROBE®



Data Sheet

CT238A Amp Clamp Accessory

Current Transformer

This current transformer probe measures AC or DC current. It converts high current to a low level millivolt signal for input directly into a test instrument. It can be used with standard DMMs, recorders, digital or analog meters, data loggers/DAS, oscilloscopes, or other test and measurement instruments.

- AC/DC current clamp, 20 A
- Special "low current" version
- Zero adjust knob

Included AccessoriesAttached leads and users manual.

No hassle warranty

No waiting.

No shipping charges.



(note: \$500 MSLP limit)









CT238A Amp Clamp Accessory

Data Sheet

General Specifications

Max Conductor Size	19 mm (0.75 in)	
Lead Length	1.5 m (59 in)	
Power	9 V battery, NEDA 1604, JIS 006P, IEC 6F22	
Battery Life	30 hours (alkaline)	
Operating Temperature Range	−0 °C to + 50 °C at < 80 % R.H.	
Storage Temperature Range	−20 °C to + 85 °C	
Temperature Coefficient	0.1 % of rdg per 10 °C	
Dimensions	55 mm x 210 mm x 30 mm (2.2 in x 8.3 in x 1.2 in)	
Weight	290 g (.64 lb.)	
Warranty	One-year	

Specifications (23 °C \pm 1 °C, < 75 % R.H.)

Function	Range	Accuracy
DC Current		
DC Current	20 A max	±(1% of rdg + 2 mA)
Meter Input Impedance	10 k Ω min. and 100 pF max.	
Division Ratio	10 to 1	
Output	1 A DC at jaws = 100 mV DC to meter	
AC Current		
DC-10 kHz	20 A	20 A (< 1 kHz): ± (1 % of rdg + 2 mA)
		20 A (1 to 20 kHz): ± (3 % of rdg + 2 mA)
Meter Input Impedance	10 k Ω min. and 100 pF max.	
Division Ratio	10 to 1	
Output	1 A AC at jaws = 100 mV AC to meter	
Overload Protection		
	500 A	
	300 V AC on uninsulated conductors	

Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2007 Amprobe Test Tools. All rights reserved. 7/2007 PN: 1646652 D-US-N Rev C

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AMPROBE: