

## SEK mezz Fe 14P THT 4.5mm PL3



Part number	09 19 514 7822
Specification	SEK mezz Fe 14P THT 4.5mm PL3
HARTING eCatalogue	https://b2b.harting.com/09195147822

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	SEK Mezzanine
Element	Female connector
Description of the contact	Straight

#### Version

Termination method	Reflow soldering termination (THR) Wave soldering termination
Connection type	PCB to PCB Motherboard to daughtercard
Number of contacts	14
Termination length	4.5 mm

### Technical characteristics

Contact rows	2
Contact spacing (termination side)	2.54 mm
Rated current	1 A
Insulation resistance	>10 <sup>9</sup> Ω
Contact resistance	≤20 mΩ
Limiting temperature	-55 +125 °C (during reflow soldering max. +240 °C for 60 s)
Insertion force	≤42 N
Withdrawal force	≤42 N
Performance level	3
Mating cycles	≥50



#### Technical characteristics

Test voltage U <sub>r.m.s.</sub>	1 kV
Isolation group	IIIa (175 ≤ CTI < 400)

#### Material properties

Material (insert)	Liquid crystal polymer (LCP)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Sn over Ni Termination side Au over Pd/Ni Mating side
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

#### Specifications and approvals

Specifications	IEC 60603-13
UL / CSA	UL 1977 ECBT2.E102079
	CSA-C22.2 No. 182.3 ECBT8.E102079

#### Commercial data

Packaging size	100
Net weight	4.03 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140212794
ETIM	EC002637
eCl@ss	27460201 PCB connector (board connector)

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## HARTING:

09195147822 9195147822