

PP-V4-CA-USB2A-PP/IP20-P-P-STR-1.5



Part number	09 45 445 1912
Specification	PP-V4-CA-USB2A-PP/IP20-P-P-STR-1.5
HARTING eCatalogue	https://b2b.harting.com/09454451912

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Series	HARTING PushPull (V4)
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING PushPull (V4) USB 2.0 Type A
Connector 2	

Version

Cable length	1.5 m
Number of cores	4
Core structure	2x AWG 26/7 2x AWG 24/11
Shielding	Shielded

Technical characteristics

Rated current	1.5 A
Rated voltage	30 V DC
Data rate	480 Mbit/s
Insulation resistance	$> 1.6 \times 10^6 \Omega$
Contact resistance	≤30 mΩ
Limiting temperature	-40 +85 °C



Technical characteristics

Insertion force	≤35 N
Withdrawal force	≥15 N
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67
Cable diameter	4.9 mm
Test voltage U _{r.m.s.}	0.5 kV (contact-contact) 0.5 kV (contact-ground)
Impedance	90 Ω ±15 %

Material properties

Liquid crystal polymer (LCP)
Copper alloy
Sn over Ni Termination side Au over Ni Mating side
PVC
Black
Polyamide (PA)
Black
V-0
compliant
compliant
е
Not contained
Not contained
Not contained
Yes
Naphthalene

Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)	
----------------	--------------------------------	--

Commercial data

Packaging size	1
Net weight	89 g

Product data sheet 09 45 445 1912 PP-V4-CA-USB2A-PP/IP20-P-P-STR-1.5



Commercial data

Country of origin	Malaysia
European customs tariff number	85444290
GTIN	5713140262720
ETIM	EC002599
eCl@ss	27060390 Ready-made data cable (unspecified)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09454451912