


| ø3.2(4 | 1x)   |
|--------|-------|
| 20.8   | ø18.1 |

| KEY POS | PART NO.       |
|---------|----------------|
| N       | RTHP0121PN-16C |
| W       | RTHP0121PW-16C |
| Х       | RTHP0121PX-16C |
| Υ       | RTHP0121PY-16C |
| Z       | RTHP0121PZ-16C |

Mounting Hole

## NOTES:

- 1. MATERIAL:
  - 1.1 HOUSING BODY: ZINC DIE-CAST, NICKEL PLATED
  - 1.2 INSULATION INSERT: PA66,UL94 V0
  - 1.3 CONTACT: COPPER ALLOY, SILVER PLATED
  - 1.4 SEAL: SILICONE RUBBER
- 2. SPECIFICATIONS:
  - 2.1 CURRENT RATING: 86 AMPS MAX.
  - 2.2 VOLTAGE RATING: 630 V AC/DC
  - 2.3 OPERATING TEMPERATURE: -40°C TO +125°C
  - 2.4 DIELECTRIC WITHSTANDING VOLTAGE:
    - LESS THAN 2 MILLIAMPS CURRENT IEAKAGE @ 5000 VOLTS AC
  - 2.5 DEGREE OF PROTECTION: IP67 (MATED CONDITION)
  - 2.6 DEGREE OF POLLUTION: 3 PER UL840
  - 2.7 OVERVOLTAGE CATEGORY: III PER UL840
  - 2.8 MATING CYCLE DURABILITY: >100 CYCLES
  - 2.9 RoHS COMPLIANT
- 3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 4. "\*" DENOTE KEY POSTION OF "N", "W", "X", "Y" OR "Z".
- 5. CONTACT P/N: MP6ARS8S



| SEE PART NUMBER   |                |  |               |  |                             |               |      |    |  |  |
|---|----------------|--|---------------|--|-----------------------------|---------------|------|----|--|--|
|   | _              | _  |               |  |                             |               |      |    |  |  |
| QUANTITY PART NUMBER  |                | DESCRIPTION  |               |  |                             |               | ITEM |    |  |  |
| MATERIALS LIST  |                |  |               |  |                             |               |      |    |  |  |
|   | WISE SPECIFIED | SIGNATURE  | RES DATE Amph |  | mnhand                      | $\overline{}$ |      |    |  |  |
| All dimensions are in metric(mn     Tolerances are as follows:     PL DEC ±0.30   Fractions +1.   |                | Drack Drack  | 08/14/14      | Amphenol   |                             |               | ) I  |    |  |  |
| 2 PL DEC ±0.15<br>3 PL DEC ±0.08  | Angles ±1°     | CHECKED:   |               | Sine Systems - www.amphenol-sine.com             |                             |               | m    | _  |  |  |
| 3) Note reference = X   |                | ENGINEER:  |               | 44724 Morley Drive<br>Clinton Township, MI 48036 |                             |               |      |    |  |  |
| MATERIAL SPECIFICA  | TIONS:         | APPROVAL:  |               |  | Clinton Township, wii 46030 |               |      |    |  |  |
|   |                | CUSTOMER:  |               | ECO-MATE,RECEPTACLE,3.6mm SINGLE PIN CONTACT,    |                             |               |      |    |  |  |
|   |                | THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES.  |               | CRIMP TYPE,FLANGE WALL MOUNTING                  |                             |               |      |    |  |  |
| PROCESS SPECIFICATIONS:  SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. |                | SPECIFICATIONS AND PERFORMANCE DATA<br>SHOWN HEREON ARE THE PROPERTY OF<br>THE AMPHENOL CORPORATION. NO RIGHTS<br>OF REPRODUCTION ARE IMPLIED. ALL |               | B  | C-                          | RTHP0121P*-16 | 1    | 31 |  |  |
|   |                | SCALE:   | 2:1           | SHEET 1  | OF                          | 1             |      |    |  |  |

DWG NO: RTHP0121P\*-16C

 ${\tt ECO-MATE, RECEPTAGLE, 3.6mm} \ {\tt SINGLE PIN CONTACT, OR IMP TYPE, FLANGE WALL MOUNTING}$ 

REV: **B1** 

SH: 1 OF

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: RTHP0121PN-16C