

RATING VOLTAGE 60 V AC/DC STORAGE HUMIDITY RANGE (NO SPECIFICATIONS ITEM TEST METHOD REQUIREMENTS CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING. MARKING CONFIRMED VISUALLY. ELECTRIC CHARACTERISTICS CONTACT RESISTANCE 1A DC. 10 mΩ MAX. CONTACT RESISTANCE 20 mV AC MAX, 0.1 mA(DC OR 1000Hz) 10 mΩ MAX. MILLIVOLT LEVEL METHOD INSULATION RESISTANCE 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ.	TO +60 °C (HUMIDITY 85% OT DEWED) Q × ×	T AT
CURRENT 1 A SPECIFICATIONS ITEM TEST METHOD REQUIREMENTS CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY. ELECTRIC CHARACTERISTICS CONTACT RESISTANCE IA DC. CONTACT RESISTANCE MILLIVOLT LEVEL METHOD INSULATION RESISTANCE VOLTAGE PROOF 650 V AC FOR 1 min. MECHANICAL OPERATION J CONTACT RESISTANCE: 20 mΩ TO MΩ MAX. 10 mΩ MAX. 100 MΩ MIN. 100 MΩ M	OT DEWED) Q	T AT
SPECIFICATIONS ITEM TEST METHOD REQUIREMENTS CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING. MARKING CONFIRMED VISUALLY. ELECTRIC CHARACTERISTICS CONTACT RESISTANCE 1A DC. 10 mΩ MAX. CONTACT RESISTANCE 1A DC. 10 mΩ MAX. MILLIVOLT LEVEL METHOD INSULATION RESISTANCE 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	Q	(×
SPECIFICATIONS ITEM TEST METHOD REQUIREMENTS CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING. MARKING CONFIRMED VISUALLY. ELECTRIC CHARACTERISTICS CONTACT RESISTANCE 1A DC. 10 mΩ MAX. CONTACT RESISTANCE 20 mV AC MAX, 0.1 mA(DC OR 1000Hz) 10 mΩ MAX. MILLIVOLT LEVEL METHOD INSULATION RESISTANCE 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	(×
ITEM TEST METHOD REQUIREMENTS CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING. MARKING CONFIRMED VISUALLY. ELECTRIC CHARACTERISTICS CONTACT RESISTANCE 1A DC. 10 mΩ MAX. CONTACT RESISTANCE 20 mV AC MAX, 0.1 mA(DC OR 1000Hz) 10 mΩ MAX. MILLIVOLT LEVEL METHOD INSULATION RESISTANCE 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	(×
CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING. MARKING CONFIRMED VISUALLY. ACCORDING TO DRAWING. ELECTRIC CHARACTERISTICS ONTACT RESISTANCE 10 mΩ MAX. CONTACT RESISTANCE 10 mΩ MAX. MAX. MILLIVOLT LEVEL METHOD 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	(×
MARKING CONFIRMED VISUALLY. ELECTRIC CHARACTERISTICS 10 mΩ MAX. CONTACT RESISTANCE 1A DC. 10 mΩ MAX. CONTACT RESISTANCE 20 mV AC MAX, 0.1 mA(DC OR 1000Hz) 10 mΩ MAX. MILLIVOLT LEVEL METHOD 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ		
ELECTRIC CHARACTERISTICS CONTACT RESISTANCE 1A DC. 10 mΩ MAX. CONTACT RESISTANCE 20 mV AC MAX, 0.1 mA(DC OR 1000Hz) 10 mΩ MAX. MILLIVOLT LEVEL METHOD 500 V DC. 100 MΩ MIN. INSULATION RESISTANCE 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	
CONTACT RESISTANCE 1A DC. 10 m Ω MAX . CONTACT RESISTANCE 20 mV AC MAX, 0.1 mA(DC OR 1000Hz) 10 m Ω MAX . MILLIVOLT LEVEL METHOD INSULATION RESISTANCE 500 V DC. 100 M Ω MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. 1 CONTACT RESISTANCE: 20 m Ω		×
CONTACT RESISTANCE 20 mV AC MAX, $0.1 \text{ mA}(\text{DC OR } 1000\text{Hz})$ $10 \text{ m}\Omega$ MAX . MILLIVOLT LEVEL METHOD 10 mS MAX . 100 M M MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. $\boxed{1}$ CONTACT RESISTANCE: $20 \text{ m}\Omega$	×	
INSULATION RESISTANCE 500 V DC. 100 MΩ MIN. VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	_
VOLTAGE PROOF 650 V AC FOR 1 min. NO BREAKDOWN. MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ		
MECHANICAL CHARACTERISTICS MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	: -
MECHANICAL OPERATION 30 TIMES INSERTIONS AND EXTRACTIONS. ① CONTACT RESISTANCE: 20 mΩ	×	· –
130 HIVE SINGENTIONS AND EXTRACTIONS.		
② NO DAMAGE, CRACK AND LOOS PARTS.		
VIBRATION FREQUENCY 20 TO 200Hz (88m/s²) ① NO ELECTRICAL DISCONTINUITY (OF 7ΩMIN, ×	· –
SWEEP TIME 3min.(ROUND TRIP) 1µs MIN. AT 3h FOR 3 DIRECTIONS. ② CONTACT RESISTANCE: 20 mΩ MA	AX. ×	
③ NO DAMAGE, CRACK AND LOOSEI		
PARTS. SHOCK 981m/s² DURATION OF PULSE 6ms AT 3 TIMES ① NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ② NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ③ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ③ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ③ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ③ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ⑤ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ⑤ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3 TIMES ⑥ NO ELECTRICAL DISCONTINUITY OF PULSE 6ms AT 3	OF 7ΩMIN . ×	
FOR 6 DIRECTIONS.	OI /SZIVIIIV,	
② NO DAMAGE, CRACK AND LOOSEI	NESS OF X	-
LOCK STRENGTH MEASURE BREAK STRENGTH OF THE LOCK BY ① 100N MIN.	_	
PULLING THE CONNECTOR IN THE MATING DIRECTION.		
ENVIRONMENTAL CHARACTERISTICS	1111	
DAMP HEAT EXPOSED AT $60 ^{\circ}$ C, $90 ^{\sim} 95 ^{\circ}$ M, $96 ^{\circ}$ h. ① CONTACT RESISTANCE: $20 ^{\circ}$ M Ω (STEADY STATE)		
③ NO DAMAGE, CRACK AND LOOS		
RAPID CHANGE OF TEMPERATURE- 40 \rightarrow ROOM TEMP \rightarrow 125°C \rightarrow (1) CONTACT RESISTANCE: 20 m Ω	MAX. ×	. –
TEMPERATURE ROOM TEMP 2 NO DAMAGE, CRACK AND LOOS	SENESS OF x	-
TIME $30 \rightarrow 5 \rightarrow 30 \rightarrow 5 \text{min}$ PARTS. UNDER 1000 CYCLES.		
DRY HEAT EXPOSED AT 140°C, 120 h. ① CONTACT RESISTANCE: $20 \text{ m}\Omega$	MAX. ×	-
② NO DAMAGE, CRACK AND LOOS	SENESS OF x	-
	MAX. ×	· –
② NO DAMAGE, CRACK AND LOOS PARTS.	SENESS OF ×	
RESISTANCE TO SO ₂ GAS EXPOSED IN 25 PPM AT 75% MIN FOR 96h. $\textcircled{1}$ CONTACT RESISTANCE: 20 m Ω	MAX. ×	: -
		+
COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED		DATE
1 DIS-T-00019375 TY. MOGI AH. EDASHIG	3E 20	231031
REMARK Note 1) "STORAGE" means a long-term storage state for the unused product. APPROVED HK. UMEH CHECKED HK. LIMEH		170522
		170522
O'LECKED TIK. OHER)170522)170522
DESIGNED YH. MAM.	l	
O'LECKED TIK. OHER	10010-00-0	vv
DESIGNED YH. MAM. DRAWN MN. SAT		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hirose Electric:

ZG05A-2224SCF