





- Notes
- ① The recommended clamp torque of REF. No. ① to be 3 to 3.5 N·m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent REF. No. ① from loosening.
 - ② The recommended clamp torque of REF. No. ④ to be 0.65 to 0.7 N·m.
 - ③ Sealing and airtightness and oil resisting shall be tested under mated condition with an applicable connector.

2	BRASS	NICKEL PLATING		4	STAINLESS STEEL	M3×0.5×8													
1	BRASS	CHROME PLATING		3	SILICONE RUBBER	(BLACK)													
NO.		MATERIAL		FINISH . REMARKS		NO.		MATERIAL		FINISH . REMARKS									
UNITS mm				SCALE 2 : 1				COUNT	DESCRIPTION OF REVISIONS			DESIGNED		CHECKED		DATE			
<div>HRSHIROSE ELECTRIC CO., LTD.</div>				APPROVED :HY. KOBAYASHI				15.08.05				DRAWING NO.				EDC-110601-72-00			
				CHECKED :HY. KOBAYASHI				15.08.05				PART NO.				JR16WCC-6(72)			
				DESIGNED :HY. KISHI				15.08.05				CODE NO.				CL114-2053-9-72			
				DRAWN :HY. KISHI				15.08.05											

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[JR16WCC-6\(72\)](#)