DC-C4-J12-F1

Product Details



Features

D-sub Connector, Junction shell (Metallic hood, Long screw #4-40), DC

Part Number	DC-C4-J12-F1
Status	Active
Number of Positions	-
Contact Pitch (mm)	
Rated Current (A)	
Rated Voltage (V)	
Applicable Specifications	
Waterproof/ Non-waterproof	
Applications	
Connector Type	Accessory
Connector Style	
Contact Type	
Wire Termination Style	
Applicable Wire Size (AWG)	
EMI Shielded	Applicable
PCB Mounting Style	
SMD Flag	

Applicable Wire Size (mm ²) Applicable Wire Size Dielectric Withstanding Voltage (VACr.m.s. Iminute) Insulation Resistance (megaohm min.) Contact Resistance (milliohm max.) Operating Temperature Range (deg. C) Shell Type Material of Insulator Finish of Contact in Connecting Area Finish of Contact in Connecting Area Mounting Area Stetter of Ferrite Applicable Product Part Numbers Applicable Contacts Applicable Product Part Numbers Applicable Product Part	Shell Size	С
Dielectric Withstanding Voltage (VACr.m.s. 1minute) Insulation Resistance (megaohm min.) Contact Resistance (milliohm max.) Operating Temperature Range (deg. C) Shell Type Shell Type Material of Insulator Contact Finish of Contact in Connecting Area Finish of Contact in PCB Mounting Area Kounting Method Screw Lock Assembly Existence of Ferrite Applicable Product Part Numbers Use with Accessories Lose with Accessories Accessory Type Numbers	Applicable Wire Size (mm ²)	
Votage (VACr.m.s.1minute)Insulation Resistance (megaohm min.)Contact Resistance (milliohm max.)Operating Temperature Range (deg. C)Shell TypeMaterial of InsulatorContactContactFinish of Contact in Connecting AreaFinish of Contact in Connecting Anounting AreaSouth Contact in PCB Mounting MethodFinish of Contact in PCB Mounting MethodFinish of Contact in PCB Mounting MethodScrew Lock AssemblyExistence of FerriteApplicable Product Part NumbersLupicable Product Part NumbersAusti AccessoriesAccessory TypeBott Screw Lock (pul)2015/863)	Applicable Wire Size	
(megaohm min.)Contact Resistance (milliohm max.)Operating Temperature Range (deg. C)Shell TypeMaterial of InsulatorContactContactContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting MethodScrew Lock AssemblyExistence of FerriteApplicable Product Part NumbersLog with AccessoriesAccessory TypeARBIn Substances (2011/65/EU, (EU)2015/683)		
max.)Operating Temperature Range (deg. C)Shell TypeMaterial of InsulatorContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting AreaScrew Lock AssemblyExistence of FerriteApplicable Product Part NumbersUse with AccessoriesAccessory TypeRoHS compliant		
(deg. c)Shell TypeMaterial of InsulatorContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting MethodScrew Lock AssemblyExistence of FerriteApplicable ContactsApplicable Product Part NumbersUse with AccessoriesAccessory TypeBoth Screw Lock JackAccessory TypeApticable ContactApplicable ContactsApplicable ContactsApplicable Product Part NumbersApplicable Product Part NumbersApplicable ContactsApplicable ContactsApplicable Product Part NumbersApplicable Product Part NumbersApplicable ContactsApplicable Product Part NumbersApplicable Product Part NumbersApplicable ContactsApplicable ContactsApplicable Product Part NumbersApplicable Product Part NumbersApplicable ContactsApplicable ContactsApplicable ContactsApplicable Product Part NumbersApplicable Product Part NumbersApplicable ContactsApplicable ContactsApplicable Product Part NumbersApplicable Product Part NumbersA		
Material of Insulator Contact Contact in Connecting Area Finish of Contact in PCB Mounting Area Screw Lock Assembly Screw Lock Assembly Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type Batter Screw Lock Josephiant		
Contact Finish of Contact in Connecting Area Finish of Contact in PCB Mounting Area Mounting Method Screw Lock Assembly Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type Both Scompliant	Shell Type	
Finish of Contact in Connecting Area Finish of Contact in PCB Mounting Area Mounting Method Screw Lock Assembly Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Vise with Accessories Accessory Type Bottom Lock Method Image: Screw Lock Assembly	Material of Insulator	
Area Finish of Contact in PCB Mounting Area Mounting Method Screw Lock Assembly Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type Both S compliant	Contact	
Mounting AreaMounting MethodScrew Lock AssemblyExistence of FerriteApplicable ContactsApplicable Product Part NumbersUse with AccessoriesAccessory TypeBoHS compliantUse with Accessories		
Screw Lock Assembly Image: Contacts Existence of Ferrite Image: Contacts Applicable Contacts Image: Contacts Applicable Product Part Image: Contacts Numbers Image: Contacts Use with Accessories Image: Contacts Accessory Type Image: Contacts Contacts Contacts Contacts RoHS compliant Image: Contacts		
Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant	Mounting Method	
Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant	Screw Lock Assembly	
Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant	Existence of Ferrite	
Numbers Image: Second Seco	Applicable Contacts	
Accessory Type RoHS compliant		
RoHS compliant 10 substances (2011/65/EU, (EU)2015/863)	Use with Accessories	
	Accessory Type	
REACH compliant	RoHS compliant	10 substances (2011/65/EU, (EU)2015/863)
	REACH compliant	
Remarks	Remarks	

Notice

 The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

- 2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
- The products presented in this web site are designed for the uses recommended below. We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.
 - (1) Applications that require consultation:

* Please contact us if you are considering use involving a quality assurance program that

you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

* We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

- (2) Recommended applications include:
 - * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JAE Electronics:

DC-C4-J12-F1