



features

- Quickly fuses to the overload
- Circuit is completely isolated after fusing
- Lightning surge test (IEC61000-4-5) effective
- Can be used in high temperature environment



dimensions and construction



Type	Dimensions inches (mm)			
	L	W	H	P
TPR1	.354±.004 (9.0±0.1)	.197±.004 (5.0±0.1)	.394±.004 (10.0±0.1)	.197±.02 (5.0±0.5)

ordering information

New Part #	TPR	1	C	T	A	100	J
	Type	Power Rating	Terminal Surface Material	Taping	Packaging	Nominal Resistance	Resistance Tolerance
		1: 1W	C: Sn-Cu	T: Taping Blank: Bulk	A: AMMO Blank: Bulk Contact factory for taping specifications	2 significant figures + 1 multiplier "R" indicates decimal on values <10Ω	J: ±5%


applications and ratings

Part Designation	Power Rating	Resistance Range	T.C.R. (x 10 ⁻⁶ /K)	Terminal Temperature Under Rated Load	Operating Temperature Range	Maximum Open-Circuit Voltage	Lightning Surge Test*	Maximum Working Voltage	Maximum Overload Voltage
		J: ±5% E24							
TPR1	1W	2Ω ~ 10kΩ	~51Ω: 200 56Ω~: 350	+125°C and less	-40°C ~ +150°C	320V a.c.	1.5kV	E=√(PxR)	E=√(PxRx2)

* Lightning surge test at 10Ω


environmental applications

Derating Curve




For resistors operated at a terminal temperature of 125°C or above, a power rating shall be derated in accordance with the above derating curve.

Fusing Characteristics



Life Estimation Curve



Performance Characteristics

Parameter	Requirement		Test Method
	Limit	Typical	
Resistance	Within specified tolerance	—	25°C
T.C.R.	Within specified T.C.R.	—	+25°C/-40°C and +25°C/+125°C
Fusing Characteristics	Within 6 seconds	—	Rated power x 10
Rapid Change of Temperature	±(5%+0.05Ω)	2%	-40°C/0.5 hr, +125°C/0.5 hr, 1000 cycles
Overload (Short Time)	±(5%+0.05Ω)	2%	Rated power x 2 for 5 seconds
Resistance to Soldering Heat	±(1%+0.05Ω)	0.3%	260°C ± 5°C, 10 ± 1 second
Endurance at 125°C and Less of Terminal Temperature	±(5%+0.05Ω)	3%	Terminal temperature: 125°C, 1.5 hr ON, 0.5 hr OFF cycle, 1000 hours

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KOA Speer:

[TPR1CTA110J](#) [TPR1CTA390J](#) [TPR1CTA820J](#) [TPR1CTA331J](#) [TPR1CTA1101J](#) [TPR1CTA3R6J](#) [TPR1CTA6R2J](#)
[TPR1CTA471J](#) [TPR1CTA621J](#) [TPR1CTA7501J](#) [TPR1CTA9101J](#) [TPR1CTA2R7J](#) [TPR1CTA6R8J](#) [TPR1CTA121J](#)
[TPR1CTA431J](#) [TPR1CTA1001J](#) [TPR1CTA6801J](#) [TPR1CTA120J](#) [TPR1CTA1801J](#) [TPR1CTA1601J](#) [TPR1CTA4701J](#)
[TPR1CTA3R0J](#) [TPR1CTA300J](#) [TPR1CTA1002J](#) [TPR1CTA201J](#) [TPR1CTA511J](#) [TPR1CTA911J](#) [TPR1CTA3R3J](#)
[TPR1CTA2001J](#) [TPR1CTA5101J](#) [TPR1CTA220J](#) [TPR1CTA131J](#) [TPR1CTA181J](#) [TPR1CTA561J](#) [TPR1CTA1301J](#)
[TPR1CTA8R2J](#) [TPR1CTA200J](#) [TPR1CTA360J](#) [TPR1CTA5R1J](#) [TPR1CTA9R1J](#) [TPR1CTA160J](#) [TPR1CTA240J](#)
[TPR1CTA470J](#) [TPR1CTA620J](#) [TPR1CTA151J](#) [TPR1CTA301J](#) [TPR1CTA5601J](#) [TPR1CTA510J](#) [TPR1CTA910J](#)
[TPR1CTA111J](#) [TPR1CTA5R6J](#) [TPR1CTA100J](#) [TPR1CTA330J](#) [TPR1CTA751J](#) [TPR1CTA6201J](#) [TPR1CTA271J](#)
[TPR1CTA391J](#) [TPR1CTA821J](#) [TPR1CTA1501J](#) [TPR1CTA3001J](#) [TPR1CTA750J](#) [TPR1CTA1201J](#) [TPR1CTA3901J](#)
[TPR1CTA4301J](#) [TPR1CTA2R2J](#) [TPR1CTA7R5J](#) [TPR1CTA221J](#) [TPR1CTA150J](#) [TPR1CTA361J](#) [TPR1CTA8201J](#)
[TPR1CTA680J](#) [TPR1CTA161J](#) [TPR1CTA3601J](#) [TPR1CTA430J](#) [TPR1CTA2201J](#) [TPR1CTA2R0J](#) [TPR1CTA4R7J](#)
[TPR1CTA681J](#) [TPR1CTA2401J](#) [TPR1CTA4R3J](#) [TPR1CTA270J](#) [TPR1CTA101J](#) [TPR1CTA2701J](#) [TPR1CTA2R4J](#)
[TPR1CTA3R9J](#) [TPR1CTA130J](#) [TPR1CTA180J](#) [TPR1CTA560J](#) [TPR1CTA241J](#) [TPR1CTA3301J](#) [TPR1CTA162J](#)
[TPR1CTA622J](#) [TPR1CTA752J](#) [TPR1CTA822J](#) [TPR1CTA102J](#) [TPR1CTA272J](#) [TPR1CTA432J](#) [TPR1CTA912J](#)
[TPR1CTA562J](#) [TPR1CTA202J](#)