

PAA.MO.7GL.AC52G

SUMMARY

Wires

Low voltage



Image is for illustrative purpose only

Series	1P
Termination type	Male solder
IP rating	50
AWG wire size	0.00 - 26.00
Cable Ø	4.00 - 5.20 mm
Status	active
Matching parts	PLA.M0.7GL.LG

7

Download <u>Request a quote</u> <u>Eplan</u> <u>Catalog</u>

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PA*: Straight plug with cable collet
Keying	2 keys (alpha=40; Plug: male contacts; Receptacle: female contacts)
Housing Material	PSU (Polysulfone), gray
Variant	G : Gray collet nut
Weight	5.14 g
Performance	

Configuration	1P.M07 : 7 Low Voltage	
Insulator	L: PEEK (UL 94 / V-0/1.5)	
Rated Current	5 Amps	

Specifications

Contact Type: Solder Contact Dia.: 0.7 mm (0.0275in) Bucket Dia.: 0.6 mm (0.024in) Max. Solid Conductor: 0.14 mm^2 (AWG 26) Max. Stranded Conductor: 0.14 mm^2 (AWG 26) R (max): 6.5 mOhm Test voltage (kV rms) Contact-contact: 1.05


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Air clearance min.: 0.85 mm Creepage distance min.: 0.85 mm

Others

Endurance (Shell): >2000 mating cycles Temp (min / max): -50°C / +150°C F ret (min): 50 N F ret (max): 150 N Steam sterilization: > 100 times (with potting on rear connection)

DRAWINGS



RECOMMENDED BY LEMO

Tools

Cables

CMN.07.T28.044PGZE		Grey	
CMN.07.T28.044PNZE			
70140	PVC	Grey	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

LEMO: PAA.M0.7GL.AC52G