

PAG.M0.4TL.AC65N

SUMMARY

Wires

Low voltage



	The second second	(Come)
18	**	
Tean	1	(-

Image is for illustrative purpose only

Series	1P
Termination type	Male solder
IP rating	50
AWG wire size	0.00 - 22.00
Cable Ø	5.30 - 6.50 mm
Status	active
Matching parts	PLG.M0.4TL.LN

Download <u>Request a quote</u> <u>Eplan</u> <u>Catalog</u>

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PA*: Straight plug with cable collet		
Keying	1 key (alpha=0; Plug: male contact; Receptacle: female contact)		
Housing Material	PEI (Polyetherimide), black		
Variant	N : Black collet nut		
Weight	5.02 g		

Performance

Configuration	1P.M04 : 4 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated Current	8 Amps

Specifications

Contact Type: Solder Contact Dia.: 0.9 mm (0.035in) Bucket Dia.: 0.8 mm (0.031in) Max. Solid Conductor: 0.34 mm^2 (AWG 22) Max. Stranded Conductor: 0.34 mm^2 (AWG 22) R (max): 4.5 mOhm Test voltage (kV rms) Contact-contact: 1.2


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Air clearance min.: 1.2 mm Creepage distance min.: 1.2 mm

Others

Endurance (Shell): >2000 mating cycles Temp (min / max): -50°C / +170°C F ret (min): 50 N F ret (max): 150 N Steam sterilization: > 100 times (with potting on rear connection)

DRAWINGS



RECOMMENDED BY LEMO

Tools

Cables

417920	PVC	Grey	
4220	PVC	Black	
CTR.75.030.121870G	PVC	Grey	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

LEMO: PAG.M0.4TL.AC65N