

SSI-LXH604HD-150





ELECTRO-OPTICAL CH	ARACTERISTICS T	4=25°C	If = 20	l mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		700		nm	
FORWARD VOLTAGE		2.1	2.5	۷f	
REVERSE VOLTAGE	5.0			٧٢	Aبر100=۱۲
AXIAL INTENSITY		10		mcd	f = 20 mA
VIEWING ANGLE		80		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED DIFFUSED				

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	120	mW
DERATE FROM 25°C	-1.2	m₩/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	•C
SOLDERING TEMP.	+ 260	• C
2.0mm FROM BODY		3 SEC. MAX

* t<10µS

NOTES:

- 1. SSL-LX509F3HD, RED LED.
- 2. SSH-LXH604 BLACK HOLDER.
- ANODE LEAD: LXP-WST24RDTOC, RED INSULATED LEAD, 24 AWG, CUT 155mm, STRIP 3mm & 9.5mm.
- 4. CATHODE LEAD: LXP-WST24BLTCC, BLACK INSULATED LEAD, 24 AWG. CUT 155mm, STRIP 3mm & 9.5mm.
- 5. STAKE LED IN HOLDER.



UNCONTROLLED DOCUMENT

*UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.001), INN==+0.000

*UNCONTROLLED DOCUMENT

*UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.003). INN==+0.000

*UNCONTROLLED DOCUMENT

*UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.003). INN==+0.000

**UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.000), LEAD LENGTH=±0.75 (±0.000). INN==+0.000

**UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.000). XXX=±0.127 (±0.000). LEAD SIZE=±0.05 (±0.000), LEAD SIZE=±0.05 (±0.000). LEAD SIZE=±0.05 (

PART NUMBER
SSI-LXH604HD-150

T-5mm PANEL INDICATOR,
700nm RED LED, RED DIFFUSED LENS,
WITH 6" WIRE LEADS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLISSINGE AND DISSEMINATION TO ALL THRO PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 03.20.08
PAGE: 1 OF 1
JN SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSI-LXH604HD-150