

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	0917161503 Active	[a Alá
Overview: Description:	ACTIVE <u>RAST 2.5 Connector System</u> 2.50mm Pitch Appli-Mate RAST 2.5 IDT Housing, Direct/Indirect, Female, 6 Circuits, Removed Position Keys C, E, F & G		all	
Documents: <u>3D Model</u> Drawing (PDF) Product Specification	Application Specification 990 Packaging Specification PK-9 PS-99020-0040-001 (PDF) RoHS Certificate of Complian	00871-001-001 (PDF)	Sorias image	- Reference only
Agency Certification CSA UL	LR19980 E29179		EU ELV Not Relevant	
General Product Family Series Comments	IDT and Solder Connectors 91716 ""This Molex product is manufi- that has the following ratings, to agencies:. a) A Glow Wire Ignit (GWIT) of at least 775 deg C p b) A Glow Wire Flammability In 850 deg C per IEC 60695-2-12 with the requirements set out in Standard IEC 60335-1 5th editi similar electrical appliances - si Resistance to heat and fire. <p using this product must determ use in their particular application other acceptable means as des glow-wire flammability test star and any applicable product end If it is determined during the cu of suitability, that higher perforr please contact Molex for possit """This Molex product is manufi- that has the following ratings, to agencies:. a) A Glow Wire Ignit of at least 775 deg C per IEC 6 Wire Flammability Index (GWF per IEC 60695-2-12.and hence requirements set out in the Inte 60335-1 5th edition - household appliances - safety, section 30 and fire. <p><p> The custome must determine its suitability for application through testing or o as described in end-product gloss standard IEC 60695-2-11 and a end-use standard(s). <p> If it is the customer's evaluation of su performance is required, please possible product options.""</p></p></p></p 	ested by independent ion Temperature er IEC 60695-2-13 dex (GWFI) above .and hence complies in the International on - household and afety, section 30 > <p> The customers ine its suitability for in through testing or scribed in end-product idard IEC 60695-2-11 d-use standard(s). <p> stomer's evaluation nance is required, ole product options.""", actured from material ested by independent ion Temperature (GWIT) 0695-2-13 b) A Glow I) above 850 deg C complies with the irmational Standard IEC d and similar electrical Resistance to heat rs using this product r use in their particular ther acceptable means ow-wire flammability test any applicable product is determined during itability, that higher</p></p>	China ROHS ELV RoHS Phthalates Search Parts in th <u>91716</u> Series Mates With	China RoHS , please visit Contact US Green Image Not Relevant Not Contained as Series 2.5 Header 90861 , 90860
Overview Product Name	RAST 2.5 Connector System RAST 2.5			

UPC Use With

Use With	RAST standard interface		
Dhusiagh			
Physical Circuits (Loaded)	6		
Circuits (maximum)	6		
Color - Resin	Natural (White)		
Durability (mating cycles max)	10		
Flammability	94V-0		
Gender			
Glow-Wire Capable	Female No		
Lock to Mating Part Material - Metal	None Bhosphor Bronzo		
	Phosphor Bronze Tin		
Material - Plating Mating	Tin		
Material - Plating Termination			
Material - Resin	Nylon		
Net Weight Number of Rows	1.553/g 1		
	•		
Packaging Type	Tray		
Panel Mount	No		
Pitch - Mating Interface	2.50mm		
Pitch - Termination Interface	2.50mm		
Plating min - Mating Plating min - Termination	1.016µm		
Polarized to Mating Part	1.016µm No		
Stackable	No		
	-20° to +120°C		
Temperature Range - Operating Termination Interface: Style	IDT or Pierce		
Wire Size AWG	22, 24		
Wile Size AWG	22, 24		
Electrical			
Current - Maximum per Contact	2.0A, 4.0A		
Voltage - Maximum	32V AC		
Solder Process Data			
Lead-freeProcess Capability	N/A		
Meterial lafe			
Material Info			
Reference - Drawing Numbers			
Application Specification	990330008-000		
Packaging Specification	PK-90871-001-001		
Product Specification	PS-99020-0040-001		
Sales Drawing	917160001-000		

822350167529

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex: 91716-1503