

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0917161521		and the state of the state of the state	
Status:	Active			A A
Overview:	RAST 2.5 Connector System		- 2123	6 6
Description:	2.50mm Pitch Appli-Mate RAST 2.5 IDT Housing, Direct/Indirect, Female, 6 Circuits, Removed Position Keys C & E		A VE	An Internet
Documents:				1 AND
<u>3D Model</u>		Application Specification 990330008-000 (PDF)		
Drawing (PDF)		Packaging Specification PK-90871-001-001 (PDF)		
Product Specification	<u>n PS-99020-0040-001 (PDF)</u>	RoHS Certificate of Compliance (PDF)	Series image	e - Reference only
Agency Certificatio	n			
CSA		LR19980	EU ELV	
UL		E29179	Not Relevant	
General			EU RoHS	China RoHS
Product Family		IDT and Solder Connectors	Compliant	
Series		<u>91716</u>	REACH SVHC	
Comments		"""This Molex product is manufactured from material	Not Contained Per	
		that has the following ratings, tested by independent	-ED/88/2018 (15	
		agencies:. a) A Glow Wire Ignition Temperature	January 2019)	
		(GWIT) of at least 775 deg C per IEC 60695-2-13	Halogen-Free	
		b) A Glow Wire Flammability Index (GWFI) above	<u>Status</u>	
		850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International	Low-Halogen	
		Standard IEC 60335-1 5th edition - household and	For more information	n, please visit <u>Contact US</u>
		similar electrical appliances - safety, section 30	China ROHS	Green Image
		Resistance to heat and fire. <p><p> The customers</p></p>	ELV	Not Relevant
		using this product must determine its suitability for	RoHS Phthalates	Not Contained
		use in their particular application through testing or		
		other acceptable means as described in end-product		
		glow-wire flammability test standard IEC 60695-2-11	Search Parts in t	his Sorios
		and any applicable product end-use standard(s). <p></p>	<u>91716</u> Series	
		If it is determined during the customer's evaluation		
		of suitability, that higher performance is required,	Mates With	
		please contact Molex for possible product options.""",		2.5 Header 90861, 90860
		"""This Molex product is manufactured from material		2.5 Treader <u>50001</u> , <u>50000</u>
		that has the following ratings, tested by independent		
		agencies:. a) A Glow Wire Ignition Temperature (GWIT)		
		of at least 775 deg C per IEC 60695-2-13 b) A Glow Wire Flammability Index (GWFI) above 850 deg C		
		per IEC 60695-2-12.and hence complies with the		
		requirements set out in the International Standard IEC		
		60335-1 5th edition - household and similar electrical		
		appliances - safety, section 30 Resistance to heat		
		and fire. <p><p> The customers using this product</p></p>		
		must determine its suitability for use in their particular		
		application through testing or other acceptable means		
		as described in end-product glow-wire flammability test		
		standard IEC 60695-2-11 and any applicable product		
		end-use standard(s). <p> If it is determined during</p>		
		the customer's evaluation of suitability, that higher		
		performance is required, please contact Molex for		
		possible product options."""		
Crimp Quality Equip	ment	Yes BAST 2.5 Connector System		
Overview Product Name		RAST 2.5 Connector System RAST 2.5		

UPC Use With

Use With	RAST standard interface
Physical	
Circuits (Loaded)	2
Circuits (maximum)	2
Color - Resin	Natural (White)
Durability (mating cycles max)	10
Flammability	94V-0
Gender	Female
Glow-Wire Capable	No
Lock to Mating Part	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Material - Resin	Nylon
Net Weight	0.994/g
Number of Rows	1
Packaging Type	Tray
Panel Mount	No
Pitch - Mating Interface	2.50mm
Pitch - Termination Interface	2.50mm
Plating min - Mating	1.016µm
Plating min - Termination	1.016µm
Polarized to Mating Part	No
Stackable	No
Temperature Range - Operating	-20° to +120°C
Termination Interface: Style	IDT or Pierce
Wire Size AWG	22, 24
Electrical	
Current - Maximum per Contact	2.0A, 4.0A
Voltage - Maximum	32V AC
Solder Process Data	
Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers	
Application Specification	990330008-000
Packaging Specification	PK-90871-001-001
Product Specification	PS-99020-0040-001
Sales Drawing	917160001-000

822348494828

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex: 91716-1521