

## This document was generated on 09/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	0918139105 Active KK® 508 Connector System 5.08mm Pitch KK® Crimp Ho	using, 5 Circuits, White, with Ramp, Glow Wire Capable	muni
Documents: <u>3D Model</u> Drawing (PDF)		Product Specification PS-99020-0087 (PDF) RoHS Certificate of Compliance (PDF)	
Agency Certificatior	I	E29179	Series image - Reference only
General Product Family Series Application Comments		Crimp Housings <u>91813</u> Power, Wire-to-Board This Molex product is manufactured from material that has the following ratings, tested by independent agencies :. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13 b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety; section 30 Resistance to heat and fire. <p><p>The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s).<p>If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options. <u>KK® 508</u> 800756784663</p></p></p>	EU ELV Not Relevant   EU RoHS Compliant China RoHS   Compliant   REACH SVHC   Not Contained Per -ED/79/2015 (17   December 2015)   Halogen-Free   Status   Not Low-Halogen   Need more information on product environmental compliance?   Email productcompliance @molex.com   Please visit the Contact Us section for any non-product compliance questions.   China ROHS Green Image   ELV Not Relevant   Search Parts in this Series   91813 Series
Physical Breakaway Circuits (maximum) Color - Resin Flammability Gender Glow-Wire Compliant Material - Resin Net Weight Number of Rows Packaging Type Panel Mount Pitch - Mating Interface Pitch - Termination In Polarized to Mating P Ports Stackable Temperature Range -	ce terface art	No 5 Natural (White) 94V-2 Female Yes Nylon 1.480/g 1 Bag No 5.08mm 5.08mm Yes 1 No See Product Specification	Mates With   KK® Header 3003 , 3061   Use With   KK® Crimp Terminal 2478 , 2578

Material Info

**Reference - Drawing Numbers** Product Specification Sales Drawing

PS-99020-0087 SD-91813-001

## This document was generated on 09/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex: 91813-9105