2		1				
THIS COPY IS PROVIDED ON A RESTRICTED BASIS A	ND IS NOT TO BE USE	ed in any w	Y DETRIMENTAL	TO THE INTERESTS	OF PANDUIT CORP.	
			PAND	UIT PART UMBER	WEIGHT	
	Ī		CTN	BZL6X6	28.4 G / EACH 063 LBS / EACH	
		2 USED	IN PROTECT C	ABLES IN 6.5"	ACCESS CABINETS. ' X 6.5" CABINET	-
	2X 7.05	OPENI 3. DIMEN 4. WITH	NGS AFTER KN Sions in par Cabinet top	OCK-OUTS HAVE ENTEHESES ARE	E BEEN REMOVED. E METRIC.), CABLE PROTECT 37.21in ² }.	
B	[179.0]	BEZEL	OPENING IS	6.1" X 6.1" {	37.21in ² }.	B
	V					
10 [2.5]	61 [15.5]			2 Ar	All All	
				pr	and the second sec	
┥ <u>┡</u> ╌╵┸╶ <u>╙</u> ᡛ╢╴┸╶ <u>╙</u> ᡛ╢╴┹└╴╶╣						
					للسطي المس	
[165.1]						
A				5" X 6.5" CABINE		
				CUSTOMER DF		
			ITEM REVISION NAME 12D3 DATASET FILE NAME	08BA/00	PANDU	
			12D308BA_DC	/00B CTNBZL6X6	MATERIAL :	
1 03–13–13 SSP DWR RN RELEASED TO PRODUCTION		1000000 4 00	UNLESS OTHER DIMENSIONAL TOLE .x ±	WISE SPECIFIED, RANCES ARE: IN [mm] .xxx ±	ABS	
		12D308BA-DC	.×× ± .02 [.5]	ANGLES : THIRD ANGLE	DRAWING NUMBER: 12D308BA -	
R 10-25-12 SSP DWR DRAWING RELEASED REV DATE BY CHK APR DESCRIPTION		ECN	DRAWN BY DATE SSP 10-25-12	PROJECTION CHK SCALE DWR 1/4	SHT 1 0F 1	SIZE A
2						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit: CTNBZL6X6