

Printed-circuit board connector - MC 0,5/ 8-G-2,5 BU - 1704571

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 4 A, number of positions: 8, pitch: 2.5 mm, color: blue, contact surface: Tin, mounting: Wave soldering




The figure shows a 10-position version of the product

Your advantages

- ✓ Well-known mounting principle allows worldwide use



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 50 pc |
| GTIN |  4 046356 728065 |
| GTIN | 4046356728065 |

Technical data

Dimensions

| | |
|--------------------------|--------------|
| Length [l] | 10.1 mm |
| Width | 21.9 mm |
| Pitch | 2.5 mm |
| Dimension a | 17.5 mm |
| Width [w] | 21.9 mm |
| Height [h] | 11.9 mm |
| Height | 8.1 mm |
| Length of the solder pin | 3.8 mm |
| Pin dimensions | 0.8 x 0.8 mm |
| Length | 10.1 mm |

General

| | |
|-----------------------|--------------|
| Range of articles | MC 0,5/...-G |
| Rated voltage (III/3) | 80 V |

Printed-circuit board connector - MC 0,5/ 8-G-2,5 BU - 1704571

Technical data

General

| | |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 4 A |
| Color | blue |
| Number of positions | 8 |

Standards and Regulations

| | |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
| | CUL |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Approvals

Approvals


Approvals


CCA / IECCEB Scheme / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized

Ex Approvals

Approval details

| | |
|--------------------|----------------|
| CCA | CCA/ DE1 34250 |
| Nominal voltage UN | 80 V |
| Nominal current IN | 4 A |

| | | | |
|--------------------|---|---|----------------|
| IECEE CB Scheme |  | http://www.iecee.org/ | DE1-56068-B1B2 |
| Nominal voltage UN | 80 V | | |
| Nominal current IN | 4 A | | |


| | | | |
|---|---|---|----------|
| VDE Gutachten mit Fertigungsüberwachung |  | http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx | 40013394 |
| Nominal voltage UN | 80 V | | |

Printed-circuit board connector - MC 0,5/ 8-G-2,5 BU - 1704571

Approvals

| | |
|--------------------------------|-----|
| | |
| Nominal current I _N | 4 A |

| | | |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

| | | | |
|--------------------------------|---|---|-----------------|
| cULus Recognized |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E60425-19930913 |
| | | B | |
| Nominal voltage U _N | | 125 V | |
| Nominal current I _N | | 4 A | |

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1704571](#)