

# Printed-circuit board connector - MSTB 2,5/5-ST GY BD:1-5 - 1710516

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 5, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: gray, contact surface: Tin



The figure shows a 10-pos. version of the product in green

#### Your advantages

- ✓ Allows connection of two conductors



### **Key Commercial Data**

Packing unit	50 pc
GTIN	4 055626 159225
GTIN	4055626159225

### Technical data

#### **Dimensions**

Length [1]	18.2 mm
Width [w]	25 mm
Height [ h ]	15 mm
Pitch	5 mm

#### General

Range of articles	MSTB 2,5/ST
Number of positions	5
Connection method	Screw connection with tension sleeve
Insulating material group	I
Rated voltage (III/2)	320 V
Nominal current I <sub>N</sub>	12 A



# Printed-circuit board connector - MSTB 2,5/ 5-ST GY BD:1-5 - 1710516

### Technical data

### General

Nominal cross section	2.5 mm <sup>2</sup>
Flammability rating according to UL 94	V0

### Standards and Regulations

Flammability rating according to UL 94	V0

### **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Approvals

Approvals			
Approvals			

EAC

Ex Approvals

## Approval details

EAC	EAC	B.01742
-----	-----	---------

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1710516