

PCB terminal block - SMKDSN 1,5/ 9-5,08 BDMC:-P24 - 1710990

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB terminal block, nominal current: 13.5 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 9, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: $45 \, ^{\circ}$, color: green



The figure shows a 10-position version of the product

Your advantages

- Allows connection of two conductors
- Angled connection enables multi-row arrangement on the PCB
- Extremely small design for the respective conductor cross section

















Key Commercial Data

Packing unit	100 pc
GTIN	4 055626 248806
GTIN	4055626248806

Technical data

Dimensions

Length [1]	12 mm
Pitch	5.08 mm
Dimension a	40.64 mm
Height	11 mm
Solder pin [P]	3.5 mm
Hole diameter	1.3 mm

General

Range of articles	SMKDSN 1,5
Insulating material group	I
Rated voltage (III/2)	400 V



PCB terminal block - SMKDSN 1,5/ 9-5,08 BDMC:-P24 - 1710990

Technical data

General

Nominal current I _N	13.5 A
Nominal cross section	1.5 mm²
Flammability rating according to UL 94	V0
Number of positions	9
Screw thread	M3

Standards and Regulations

Flammability rating according to UL 94	I V0
, , ,	

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 @ - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1710990