

Printed-circuit board connector - MSTB 2,5/16-ST-5,08 2CPBD:-48 - 1711772

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 16, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin



The figure shows a 10-position version of the product

Your advantages

- Well-known connection principle allows worldwide use
- ☑ Low temperature rise, thanks to maximum contact force
- Allows connection of two conductors



Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 258102
GTIN	4055626258102

Technical data

Dimensions

Length [1]	18.3 mm
Width [w]	81.28 mm
Height [h]	15 mm
Pitch	5.08 mm
Dimension a	76.2 mm

General

Range of articles	MSTB 2,5/ST
Number of positions	16
Connection method	Screw connection with tension sleeve
Insulating material group	l



Printed-circuit board connector - MSTB 2,5/16-ST-5,08 2CPBD:-48 - 1711772

Technical data

General

Rated voltage (III/2)	320 V	
Nominal current I _N	12 A	
Nominal cross section	2.5 mm ²	
Flammability rating according to UL 94	V0	
Screw thread	M3	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: <u>1711772</u>