

Printed-circuit board connector - MSTB 2,5/12-STF-5,08 BD:-M6 - 1712379

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 12, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin



The figure shows a 10-position version of the product

Your advantages

- Well-known connection principle allows worldwide use
- ☑ Low temperature rise, thanks to maximum contact force
- Screwable flange for superior mechanical stability
- Mallows connection of two conductors



Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 282466
GTIN	4055626282466

Technical data

Dimensions

Length [1]	18.3 mm
Width [w]	20.17 mm
Height [h]	15 mm
Pitch	5.08 mm
Dimension a	55.88 mm

General

Range of articles	MSTB 2,5/STF
Number of positions	12
Connection method	Screw connection with tension sleeve



Printed-circuit board connector - MSTB 2,5/12-STF-5,08 BD:-M6 - 1712379

Technical data

General

1
320 V
12 A
2.5 mm ²
V0
M3
V0
Lead 7439-92-1
Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1712379