

Printed-circuit board connector - ZEC 1,5/5-ST-5,0 C1,3 R1,5 - 1712428

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows a 10-position

PCB direct plug, nominal current: 10 A, rated voltage (III/2): 320 V, number of positions: 5, pitch: 5 mm, connection method: Spring-cage connection, color: green, contact surface: Tin, mounting: Direct plug-in method

Your advantages

version of the product

- ☑ Defined contact force ensures that contact remains stable over the long term
- ☑ Inexpensive direct plug-in connection with just one component
- Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- Plug-in direction parallel to the PCB



Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 307008
GTIN	4055626307008

Technical data

Dimensions

Width [w]	21.4 mm
Pitch	5 mm
Dimension a	20 mm

General

Range of articles	ZEC 1,5/ST
Number of positions	5
Connection method	Spring-cage connection
Insulating material group	I
Rated voltage (III/2)	320 V
Nominal current I _N	10 A



Printed-circuit board connector - ZEC 1,5/5-ST-5,0 C1,3 R1,5 - 1712428

Technical data

General

Nominal cross section	1.5 mm ²
Flammability rating according to UL 94	V0
Standards and Regulations	
Flammability rating according to UL 94	V0
Environmental Product Compliance	
China RoHS	Environmentally friendly use period: unlimited = FELIP-e

No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1712428