

Feed-through header - PC 6-16/ 3-G1-10,16 BK CP1,3 - 1712498

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 76 A, rated voltage (III/2): 1000 V, number of positions: 3, pitch: 10.16 mm, color: black, contact surface: Silver, mounting: Soldering




The figure shows a 5-pos. version of the product

Your advantages

- ✓ Well-known mounting principle allows worldwide use
- ✓ Maximum flexibility when it comes to device design – one header for connectors with different connection technologies



Key Commercial Data

Packing unit	50 pc
GTIN	 4 055626 288710
GTIN	4055626288710

Technical data

Dimensions

Length [l]	34 mm
Pitch	10.16 mm
Dimension a	20.32 mm
Height [h]	13.4 mm
Height	17.4 mm
Length of the solder pin	4 mm
Pin dimensions	1 x 1.2 mm
Pin spacing	10.16 mm
Length	34 mm

General

Range of articles	PC 6-16/..-G1
Insulating material group	I

Feed-through header - PC 6-16/ 3-G1-10,16 BK CP1,3 - 1712498

Technical data

General

Rated voltage (III/2)	1000 V
Nominal current I _N	76 A (41 A in combination with PC 6 plug)
Flammability rating according to UL 94	V0
Color	black
Number of positions	3

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals


Approvals


Approvals

IECEE CB Scheme / SEV / cULus Recognized

Ex Approvals


Approval details

IECEE CB Scheme		http://www.iecee.org/	CH-8077
Nominal voltage U _N	1000 V		
Nominal current I _N	76 A		

SEV		https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html	IK-3431
Nominal voltage U _N	1000 V		
Nominal current I _N	76 A		

Feed-through header - PC 6-16/ 3-G1-10,16 BK CP1,3 - 1712498

Approvals

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-20040202	
	D	B	C
Nominal voltage UN	600 V	300 V	300 V
Nominal current IN	5 A	66 A	66 A

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1712498](#)