


## PCB terminal block - GSMKDSPL 1,5/ 3-7,62 - 1733541

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB terminal block, nominal current: 17.5 A, pitch: 7.62 mm, number of positions: 3, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 35 °, color: green



## Key Commercial Data

| Packing unit | 50 pc           |
|--------------|-----------------|
| GTIN         | 4 017918 231835 |
| GTIN         | 4017918231835   |

## Technical data

### Item properties

| Number of positions   | 3              |
|-----------------------|----------------|
| Drive form screw head | Slotted (L)    |
| Screw thread          | M3             |
| Pin layout            | Linear pinning |

### Dimensions for the product

| Length [1]                  | 13.4 mm  |
|-----------------------------|----------|
| Width [ w ]                 | 22.86 mm |
| Height [ h ]                | 19.5 mm  |
| Pitch                       | 7.62 mm  |
| Height (without solder pin) | 16 mm    |
| Solder pin [P]              | 3.5 mm   |
| Dimension a                 | 15.24 mm |

### Dimensions for PCB design

| Hole diameter | 1.3 mm |
|---------------|--------|
|               |        |

### Packaging information

| Type of packaging                     | packed in cardboard |
|---------------------------------------|---------------------|
| Pieces per package                    | 50                  |
| Denomination packing units            | Pcs.                |
| Air clearances and creepage distances |                     |

#### Air clearances and creepage distances

| Voltage 500 V | . enage |  | 500 V |
|---------------|---------|--|-------|
|---------------|---------|--|-------|



## PCB terminal block - GSMKDSPL 1,5/ 3-7,62 - 1733541

## Technical data

### Standards and Regulations

| Connection in acc. with standard | EN-VDE  |
|----------------------------------|---|
| Environmental Product Compliance |   |
| REACh SVHC                       | Lead 7439-92-1  |
| China RoHS                       | Environmentally Friendly Use Period = 50                      |
|                                  | For details about hazardous substances go to tab "Downloads", |

Category "Manufacturer's declaration"

## Approvals

Approvals

### Approvals

EAC

### Ex Approvals

| Approval | details |
|----------|---------|
|----------|---------|

EAC

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

EHC

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com B.01742

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1733541