

Printed-circuit board connector - DFK-PC 4/ 3-G-7,62-LOE PC4MET - 1778214

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Feed-through header, nominal current: 15 A, number of positions: 3, pitch: 7.62 mm, connection method: Solder connection, color: green, contact surface: Tin

Your advantages

- Permanent solder connection prevents inadvertent loosening
- Space-saving connection
- Cable connection on the inside of the device enables flexible positioning of the panel feed-through



Key Commercial Data

Packing unit	50 pc
GTIN	 4 046356 522601
GTIN	4046356522601

Technical data

Dimensions

Pitch	7.62 mm
Dimension a	15.24 mm
Height	14 mm

General

Range of articles	DFK-PC 4/...-G -LOE
Rated voltage (III/3)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	15 A
Color	green
Number of positions	3

Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Printed-circuit board connector - DFK-PC 4/ 3-G-7,62-LOE PC4MET - 1778214

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1778214](#)