

Printed-circuit board connector - MSTBVAL 2,5/20-G-5,08 - 1801541

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB headers, nominal current: 12 A, number of positions: 20, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering



The figure shows a 10-position version of the product

Your advantages

- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- Well-known mounting principle allows worldwide use
- ✓ Vertical connection enables multi-row arrangement on the PCB
- ☑ Closed contour for optimum stability of the plug-in connection











Key Commercial Data

Packing unit	50 pc	
GTIN	4 017918 959951	
GTIN	4017918959951	

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	96.52 mm
Height	12 mm
Length of the solder pin	5 mm
Pin dimensions	1 x 1 mm

General

Range of articles	MSTBVA 2,5/G
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A



Printed-circuit board connector - MSTBVAL 2,5/20-G-5,08 - 1801541

Technical data

Color	green		
Number of positions	20		
Standards and Regulations			
Connection in acc. with standard	EN-VDE		
Environmental Product Compliance			
China RoHS	Environmentally friendly use period: unlimited = EFUP-e		
	No hazardous substances above threshold values		

Approvals

Approvais		
Approvals		

EAC

Ex Approvals

Approval details

EAC [A[B.01742
---------	---------

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1801541