

## Inline function terminal - IB IL SSI-PAC - 2861865

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Inline measurement terminal block for positioning control and absolute position encoders, complete with accessories, 1 absolute encoder input, 4 digital inputs 24 V DC, 4 digital outputs 24 V DC, 500 mA, 3-wire connection method

### Your advantages

- Startup using hand-held operator panel mode
- 5 V and 24 V encoder supply including monitoring
- 24 V sensor supply including monitoring
- Integrated monitoring functions
- Software limit switch
- Adjustable encoder offset
- Encoder resolution up to 26 bits
- Gear ratio can be parameterized
- Position detection using absolute encoders with SSI interface
- 4 digital outputs
- 3 digital inputs



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 894566
GTIN	4017918894566

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---------------------------------------------------------------------------

#### Dimensions

Width	48.8 mm
Height	140.5 mm
Depth	71.5 mm

# Inline function terminal - IB IL SSI-PAC - 2861865

## Technical data

### Interfaces

Interface	Inline local bus
Connection method	Inline data jumper

### Power supply

I/O voltage	24 V DC
I/O voltage range	19.2 V DC ... 30 V DC
Encoder supply voltage	5 V DC
	24 V DC
Encoder supply current	500 mA
	500 mA
Drawing encoder supply voltage	Main circuit $U_M$

### Electrical isolation

Test section	5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	7.5 V supply (bus logic)/functional ground of the encoder supply 500 V AC 50 Hz 1 min.
	24 V supply (I/O)/functional ground 500 V AC 50 Hz 1 min.
	24 V supply (I/O)/functional ground of the encoder supply 500 V AC 50 Hz 1 min.
	Functional ground of the encoder supply/functional ground 500 V AC 50 Hz 1 min.

### Absolute encoder input

Number of inputs	1
Adjustable resolution	26 bit (maximum)
Transmission frequency	400 kHz

### Inputs

Number of inputs	3
Connection technology	3-wire
Input voltage	24 V DC

### Outputs

Number of outputs	4
Connection technology	3-conductor (shielded)
Output voltage	24 V DC

### General

Weight	210 g
Number of plugs	1

### Inline potentials

# Inline function terminal - IB IL SSI-PAC - 2861865

## Technical data

### Inline potentials

Designation	Communications power ( $U_L$ )
Supply voltage	7.5 V DC (via voltage jumper)
Current consumption	max. 60 mA
Designation	Main circuit supply ( $U_M$ )
Supply voltage	24 V DC (via voltage jumper)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current consumption	max. 1 A
Designation	Segment circuit supply ( $U_S$ )
Supply voltage	24 V DC (via voltage jumper)
Current consumption	max. 2 A

### Standards and Regulations


Connection in acc. with standard	CUL
----------------------------------	-----

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values


## Drawings

Connection diagram



# Inline function terminal - IB IL SSI-PAC - 2861865

Dimensional drawing



## Classifications

eCl@ss

eCl@ss 10.0.1	27242605
eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27250300
eCl@ss 5.1	27242600
eCl@ss 6.0	27242600
eCl@ss 7.0	27242605
eCl@ss 8.0	27242605
eCl@ss 9.0	27242605

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601
ETIM 5.0	EC001601
ETIM 6.0	EC001601
ETIM 7.0	EC001601

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404

# Inline function terminal - IB IL SSI-PAC - 2861865

## Classifications

### UNSPSC

UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	32151602
UNSPSC 18.0	32151602
UNSPSC 19.0	32151602
UNSPSC 20.0	32151602
UNSPSC 21.0	32151602

## Approvals

### Approvals

#### Approvals

UL Recognized / EAC

#### Ex Approvals

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 140324
---------------	--	-------------------------------------------------------------------------------------------------------------------------------------------------------	---------------

EAC		EAC-Zulassung
-----	--	---------------

## Accessories

### Accessories

#### Terminal marking

Insert strip - ESL 62X10 - 0809492



Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems: Laser printer, mounting type: insert, lettering field size: 62 x 10 mm, Number of individual labels: 72

## Inline function terminal - IB IL SSI-PAC - 2861865

### Accessories

User manual - IB IL SSI UM - 2698452



User Manual, German, for Inline positioning terminals

---

User manual - IB IL SSI UM E - 2698465



User Manual, English, for Inline positioning terminals

---

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2861865](#)