

# Sensor/actuator cable - SAC-3P-M12MS/1,5-PUR/C-1L-Z - 1400786

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/actuator cable, 3-position, PUR, black RAL 9005, Plug straight M12, A-coded, on Valve connector C (8 mm), with 1 LED, connected with Z diode, connected with Z diode, cable length: 1.5 m

As illustrated, but without SPEEDCON



## Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 1 pc          |
| GTIN         |               |
| GTIN         | 4046356511599 |

## Technical data

### Dimensions

|                 |       |
|-----------------|-------|
| Length of cable | 1.5 m |
|-----------------|-------|

### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
|                                 | -20 °C ... 85 °C (valve plug)    |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

### General

|                       |                               |
|-----------------------|-------------------------------|
| Rated current at 40°C | 4 A                           |
| Rated voltage         | 24 V AC                       |
|                       | 24 V DC                       |
| Number of positions   | 3                             |
| Insulation resistance | ≥ 100 MΩ                      |
| Coding                | A - standard                  |
| Standards/regulations | M12 connector IEC 61076-2-101 |
|                       | Valve connector EN 175301-803 |

# Sensor/actuator cable - SAC-3P-M12MS/1,5-PUR/C-1L-Z - 1400786

## Technical data

### General

|                              |         |
|------------------------------|---------|
| Status display               | 1 LED   |
| Protective circuit/component | Z diode |
| Overvoltage category         | III     |
| Degree of pollution          | 3       |
| Insertion/withdrawal cycles  | ≥ 100   |

### Material

|  |                              |
|--|------------------------------|
| Flammability rating according to UL 94 | HB                           |
| Contact material                       | CuSn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | TPU GF                       |
| Material of grip body                  | TPU                          |
| Valve plug contact material            | CuSn                         |
| Valve plug contact surface material    | Sn                           |
| Valve plug contact insert material     | PA 6.6                       |
| Material housing valve plug            | TPU                          |
| Material, knurls                       | Zinc die-cast, nickel-plated |
| Sealing material                       | TPU (Seal molded)            |

### Standards and Regulations

|  |                 |
|--|-----------------|
| Standard designation                   | M12 connector   |
| Standards/regulations                  | IEC 61076-2-101 |
| Standard designation                   | Valve connector |
| Standards/regulations                  | EN 175301-803   |
| Flammability rating according to UL 94 | HB              |

### Cable

|   |                                |
|---|--------------------------------|
| Cable type                                  | PUR halogen-free black         |
| Cable type (abbreviation)                   | PUR                            |
| Cable abbreviation                          | Li9Y11Y-HF                     |
| UL AWM style                                | 20549                          |
| Conductor cross section                     | 3x 0.5 mm <sup>2</sup>         |
| AWG signal line                             | 20                             |
| Conductor structure signal line             | 28x 0.15 mm                    |
| Core diameter including insulation          | 1.5 mm ±0.05 mm (Signal line)  |
| Wire colors                                 | black 1, black 2, green/yellow |
| Overall twist                               | 3 wires, twisted               |
| External sheath, color                      | black-gray RAL 7021            |
| External cable diameter D                   | 4.5 mm ±0.2 mm                 |
| Smallest bending radius, fixed installation | 22.5 mm                        |
| Number of bending cycles                    | 15000000                       |
| Bending radius                              | 50 mm                          |

# Sensor/actuator cable - SAC-3P-M12MS/1,5-PUR/C-1L-Z - 1400786

## Technical data

### Cable


|                                 |  |
|---------------------------------|--|
| Traversing path                 | 0.9 m  |
| Traversing rate                 | 5 m/s  |
| Acceleration                    | 30 m/s <sup>2</sup>  |
| Outer sheath, material          | PUR  |
| Material conductor insulation   | PP   |
| Conductor material              | Bare Cu litz wires   |
| Insulation resistance           | min. 20 MΩ*km  |
| Conductor resistance            | 39 Ω/km (at 20 °C)   |
| Nominal voltage, cable          | ≤ 300 V  |
| Test voltage, cable             | ≥ 1200 V   |
| Flame resistance                | according to DIN VDE 0482                                  |
|                                 | According to DIN EN 50265-2-1                              |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815                   |
| Other resistance                | largely oil-resistant                                      |
|                                 | partly UV-resistant in accordance with DIN EN ISO 4892-2-A |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)               |
|                                 | -20 °C ... 80 °C (cable, flexible installation)            |

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |


## Drawings

Schematic diagram



Pin assignment M12 plug, 3-pos., valve connector


Schematic diagram



Valve connector connector pin assignment, type C


# Sensor/actuator cable - SAC-3P-M12MS/1,5-PUR/C-1L-Z - 1400786

Cable cross section




PUR halogen-free black [PUR]

Dimensional drawing




Valve connector, type C

Dimensional drawing




Plug, M12 x 1, straight, shielded

Dimensional drawing



Valve connector, type C, side view

Circuit diagram



Contact assignment of M12 plug and valve connector

## Approvals

Approvals

Approvals


CSAus

Ex Approvals

Approval details

## Sensor/actuator cable - SAC-3P-M12MS/1,5-PUR/C-1L-Z - 1400786

### Approvals

|                    |   |   |       |
|--------------------|---|---|-------|
| CSAus              |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
| Nominal voltage UN |   | 24 V  |       |
| Nominal current IN |   | 4 A   |       |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1400786](#)