


Cable connector - RC-12S2N1280FA - 1599743

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable connector, straight, shielded: yes, Screw locking, M23, No. of pos.: 12, type of contact: Socket, Solder connection, cable diameter range: 9.5 mm ... 10.5 mm





Key Commercial Data

| Packing unit | 20 pc | |
|--------------|-----------------|--|
| GTIN | 4 046356 227223 | |
| GTIN | 4046356227223 | |

Technical data

Data of the insulating body

| Coding | N |
|--|----------------------|
| Insertion/withdrawal cycles mechanical | 50 |
| Contact connection method | Solder connection |
| Type of contacts | Socket |
| Application | Signal |
| Number of positions | 12 |
| Contact diameter of power contacts | 1 mm |
| Litz wire cross section of power contacts min. | 0.08 mm ² |
| Litz wire cross section of power contacts max. | 1 mm ² |
| Nominal current per power contact at 25°C | 8 A |
| Nominal voltage, power contact | 150 V |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | 11 |
| Degree of pollution | 3 |
| Overvoltage category | II |

12/06/2018 Page 1 / 3



Cable connector - RC-12S2N1280FA - 1599743

Technical data

Data of the insulating body

| Degree of pollution | 3 |
|---------------------|---|
| Housing data | |

| Housing material | Metal |
|--|---------------|
| Type of locking | Screw locking |
| Degree of protection (when plugged in) | IP67 |
| Thread type | M23 |

Cable seal data

| Cable diameter | 9.5 mm 10.5 mm |
|------------------|----------------|
| Sealing material | NBR |

Environmental Product Compliance


| REACh SVHC | Lead 7439-92-1 |
|------------|--|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Schematic diagram

Dimensional drawing





Approvals

Approvals

| | | | |
|--------------|------|--|------|
| Approvals | | | |
| EAC | | | |
| | | | |
| Ex Approvals | | | |
| | | | |

Approval details



Cable connector - RC-12S2N1280FA - 1599743

Approvals

EAC **ERI** B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1599743