## 8501KPR12P14V24

Plug in relay, 8 pin, DPDT, 10 amp at 277 VAC, 240 VAC coil, pilot light



Product availability: Stock - Normally stocked in distribution facility



e
hen relay energised
ton

Com	-		1
L.Am	വല	me	ntarv
OULL	$\mathbf{p}_{\mathbf{i}}\mathbf{c}$		nicary

Horsepower rating	1 hp at 277 V	
	0.33 hp at 120 V	
Breaking capacity	3 A at 120 V AC - inductive control circuit per UL 508	
	1.5 A at 240 V AC - inductive control circuit per UL 508	
	10 A at 277 V AC - resistive control circuit per UL 508	
	10 A at 30 V DC - resistive control circuit per UL 508	
Maximum switching voltage	300 V at AC	
	30 V at DC	
Contact material	Silver alloy (AgNi)	
Operating time	20 ms - pick-up	
	20 ms - drop-out	
Shape of pins	Tubular	
For use with	8501NR51	
	8501NR52	

#### Environment

Liviloriment	
Ambient temperature range - operational	-40131 °F
Product certifications	CE RoHS UL listed UL recognized CSA
Height	2.66 in
Width	1.4 in
Depth	1.4 in

#### Ordering and shipping details

Category	21141 - 8501 KP	
Discount Schedule	CP2	
GTIN	00785901286073	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.209999999999999	
Returnability	Υ	
Country of origin	CN	

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: 8501KPR12P14V24