## XZCRB151141C5

jumper cable -male straight M12 4 pin-female straight M12 4 pin-PUR shielded 5m

Product availability: Non-Stock - Not normally stocked in distribution facility



Main		
Accessory / separate part category	Cabling accessory	
Accessory / separate part type	Jumper cable	

Complementary

Complementary		
Jumper cable end 1	M12 male, :4 pins (straight), fixing: screw-on	
Jumper cable end 2	M12 female, :4 pins (straight), fixing: screw-on	
Collar material	Metal	
Cable composition	4 x 0.34 mm²	
Cable length	16.4 ft (5 m)	
Wire insulation material	PUR (shielded cable)	
Cable outer diameter	0.23 in (5.9 mm)	
System Voltage	250 V AC 300 V DC	
Line Rated Current	4 A	
Insulation resistance	>= 1000 MOhm	
Resistance across terminals	<= 5000 mOhm	
Product weight	1.1 lb(US) (0.5 kg)	

#### Environment

LIMITORITICITE	
IP degree of protection	IP67 IP65
Ambient air temperature for operation	-13176 °F (-2580 °C) (static)
Ambient air temperature for storage	-13176 °F (-2580 °C)

#### Ordering and shipping details

22483 - MACHINE CABLES	
DS3	
003389119621793	
1	
0.230000000000001	
N	
CZ	
_	DS3 003389119621793 1 0.2300000000000001 N


### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

# Product data sheet Dimensions Drawings

# XZCRB151141C5

#### **Dimensions**



## Product data sheet Connections and Schema

# XZCRB151141C5

#### Connections and Schemes







# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCRB151141C5