XZCRV1512040A2

jumper cable XZ - male straight M12 3-pin - female elbowed M12 3-pin - PVC 2m

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

Complementary		
Jumper cable end 1	M12 male, :3 pins (straight), fixing: screw-on	
Jumper cable end 2	M12 female, :3 pins (elbowed), fixing: screw-on	
Collar material	Metal	
Cable composition	3 x 0.25 mm²	
Cable length	6.56 ft (2 m)	
Wire insulation material	PVC	
Cable outer diameter	0.18 in (4.6 mm)	
System Voltage	250 V AC 300 V DC	
Line Rated Current	3 A	
Insulation resistance	>= 1000 MOhm	
Resistance across terminals	<= 5000 mOhm	
Product weight	0.22 lb(US) (0.1 kg)	

Environment

IP degree of protection	IP65 IP67	
Product certifications	cULus	
Ambient air temperature for operation	-13176 °F (-2580 °C) (static)	
Ambient air temperature for storage	-13176 °F (-2580 °C)	

Ordering and shipping details

Category	22483 - MACHINE CABLES	
Discount Schedule	DS3	
GTIN	00785901076681	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.1799999999999999	
Returnability	N	
Country of origin	PL	

Offer Sustainability


RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months

XZCRV1512040A2

Dimensions




L: Lenght of cable

Product data sheet Connections and Schema

XZCRV1512040A2

Connections and Schemes



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCRV1512040A2