Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range of product	Harmony XAP
Product or component type	Protective rear cover
Device short name	XAPE
Product destination	For front plate XAPE305
Material	Insulated material
Cable entry	Knock-out cable entries
Product mounting	Flush mounting
IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010
Resistance to chemical agents	Good resistant to acetone Good resistant to alcohols Good resistant to chloride and fluoride solvents Good resistant to diluted mineral acids Good resistant to oils and petrol Good resistant to organic acids Good resistant to salts

Complementary

Product weight	0.18 lb(US) (0.08 kg)	

Environment

Environment		
Protective treatment	TC TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030	

Ordering and shipping details

Category	22475 - WALL STATIONS
Discount Schedule	CS2
GTIN	00785901992813
Nbr. of units in pkg.	1
Package weight(Lbs)	0.2800000000000003
Returnability	N
Country of origin	FR

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XAPE905