XAPM5512

empty control station - XAP-M - metal - 12 openings in 2 columns

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Harmony XAP
Die-cast empty control station
XAPM
For Ø 22 mm control and signalling units
85 x 310 mm
2.93 in (74.5 mm)
12 cut-outs
Blue
Blue
Aluminium alloy
1 hole without blanking plug for cable gland with <= 0.94 in (24 mm)
Flush mounting
IP69 conforming to NF C 20-010 IP65 conforming to IEC 60529 IP69K

Complementary

Number of vertical rows	2	
Product weight	1.74 lb(US) (0.79 kg)	

Environment

Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
Electrical shock protection class	Class I conforming to IEC 60536
	Class I conforming to NF C 20-030

Ordering and shipping details

Category	22475 - WALL STATIONS	
Discount Schedule	CS2	
GTIN	00785901313007	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.02	
Returnability	N	
Country of origin	FR	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Warranty period

18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XAPM5512