Product data sheet Characteristics

XCSL764F3Z1 INTERLOCK LIMIT SWITCH 300 VAC 10 AS XCSL

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Preventa Safety detection
Safety switch
XCSL
Key operated turret head

Complementary

Positive opening With NC contact Supply voltage type AC/DC Supply frequency 50/60 Hz Load factor 1 Power consumption in VA 10 VA (inrush) 10 VA (sealed) Signalling circuit consumption 7 mA Mechanical durability >= 1000000 cycles Maximum load current <= 15 A [Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with conforming to EN/ISO 13849-1		
Supply frequency Load factor Power consumption in VA 10 VA (inrush) 10 VA (sealed) Signalling circuit consumption 7 mA Mechanical durability >= 1000000 cycles Maximum load current <= 15 A [Uimp] rated impulse withstand voltage Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with the position of the correctly with the appropriate monitoring system and c	sitive opening	NC contact
Load factor Power consumption in VA 10 VA (inrush) 10 VA (sealed) Signalling circuit consumption 7 mA Mechanical durability >= 1000000 cycles Maximum load current (= 15 A [Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly w	oply voltage type	C
Power consumption in VA 10 VA (inrush) 10 VA (sealed) Signalling circuit consumption 7 mA Mechanical durability >= 1000000 cycles Maximum load current <= 15 A [Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly with the appro	oply frequency	Hz
Signalling circuit consumption 7 mA Mechanical durability >= 1000000 cycles Maximum load current <= 15 A [Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with the appropriate monitorin	ad factor	
Mechanical durability >= 1000000 cycles Maximum load current <= 15 A [Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly appropriate monitoring system and correctly with the appropriate monitoring system and correctly appropriate monitoring system and correctly appropriate monitoring system an	wer consumption in VA	
Maximum load current <= 15 A [Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly w	nalling circuit consumption	
[Uimp] rated impulse withstand voltage 6 kV conforming to EN/IEC 60947-5-1 Protection type Overvoltage protection signalling circuit 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with the appropriate monitoring system and c	chanical durability	00000 cycles
Protection type Overvoltage protection signalling circuit Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with	ximum load current	A
Operating rate 10 cyc/mn for maximum durability Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with th	np] rated impulse withstand voltage	conforming to EN/IEC 60947-5-1
Safety level Can reach category 4 with the appropriate monitoring system and correctly conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly appropriate monitoring	tection type	voltage protection signalling circuit
conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly with	erating rate	c/mn for maximum durability
Can reach SIL 3 with the appropriate monitoring system and correctly wire forming to EN/IEC 61508	ety level	each PL = e with the appropriate monitoring system and correctly wired rming to EN/ISO 13849-1 each SIL 3 with the appropriate monitoring system and correctly wired con-

Environment

Protective treatment	TC
Electrical shock protection class	Class I conforming to EN/IEC 60536

Ordering and shipping details

Category	18488 - INDUSTRIAL APPS-NON-NEGOTIABLE-T
Discount Schedule	Т
GTIN	00785901505884
Nbr. of units in pkg.	1
Package weight(Lbs)	2.200000000000002
Returnability	N
Country of origin	ID

Offer Sustainability

Will not be compliant
Reference not containing SVHC above the threshold
Need no specific recycling operations
WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XCSL764F3Z1