


## 3 A - 100 V power Schottky rectifier



### Features

- Negligible switching losses
- High junction temperature capability
- Low leakage current
- Good trade-off between leakage current and forward voltage drop
- Avalanche capability specified
- **ECOPACK2** compliant

### Applications

- Switching diode
- SMPS
- DC/DC converter
- LED lighting

### Description

This 100 V power Schottky rectifier is ideal for switch mode power supplies, for 12 V rails and high frequency converters.

Packaged in SMB and SMB Flat, the **STPS3H100** is optimized for use in consumer and computer applications where low drop forward voltage is required to reduce power dissipation.

#### Product status link

[STPS3H100](#)

#### Product summary

|              |        |
|--------------|--------|
| $I_{F(AV)}$  | 3 A    |
| $V_{RRM}$    | 100 V  |
| $T_j$ (max.) | 175 °C |
| $V_F$ (typ.) | 0.63 V |

# 1 Characteristics

**Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)**

| Symbol      | Parameter   |                                | Value  | Unit |   |
|-------------|---|--------------------------------|--|------|---|
| $V_{RRM}$   | Repetitive peak reverse voltage                       |                                | 100  | V    |   |
| $I_{F(AV)}$ | Average forward current, $\delta = 0.5$ square wave   | SMB $T_I = 115\text{ °C}$      | 3  | A    |   |
|             |   | SMB Flat $T_I = 140\text{ °C}$ |  |      |   |
| $I_{FSM}$   | Surge non repetitive forward current                  |                                | $t_p = 10\text{ ms}$ sinusoidal                          | 75   | A |
| $P_{ARM}$   | Repetitive peak avalanche power                       |                                | $t_p = 10\text{ }\mu\text{s}$ ,<br>$T_j = 125\text{ °C}$ | 172  | W |
| $T_{stg}$   | Storage temperature range                             |                                | -65 to +175  | °C   |   |
| $T_j$       | Maximum operating junction temperature <sup>(1)</sup> |                                | 175  | °C   |   |

1.  $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$  condition to avoid thermal runaway for a diode on its own heatsink.

**Table 2. Thermal resistance parameter**

| Symbol        | Parameter        |          | Max. value | Unit |
|---------------|------------------|----------|------------|------|
| $R_{th(j-l)}$ | Junction to lead | SMB      | 25         | °C/W |
|               |                  | SMB Flat | 15         |      |

For more information, please refer to the following application note:

- AN5088: Rectifiers thermal management, handling and mounting recommendations

**Table 3. Static electrical characteristics**

| Symbol      | Parameter               | Test conditions       |                    | Min. | Typ. | Max. | Unit          |
|-------------|-------------------------|-----------------------|--------------------|------|------|------|---------------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25\text{ °C}$  | $V_R = V_{RRM}$    | -    |      | 1.00 | $\mu\text{A}$ |
|             |                         | $T_j = 125\text{ °C}$ |                    | -    | 0.40 | 1.00 | mA            |
| $V_F^{(2)}$ | Forward voltage drop    | $T_j = 25\text{ °C}$  | $I_F = 3\text{ A}$ | -    |      | 0.84 | V             |
|             |                         | $T_j = 125\text{ °C}$ |                    | -    | 0.63 | 0.68 |               |
|             |                         | $T_j = 25\text{ °C}$  | $I_F = 6\text{ A}$ | -    |      | 0.92 |               |
|             |                         | $T_j = 125\text{ °C}$ |                    | -    | 0.71 | 0.76 |               |

1. Pulse test:  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$

2. Pulse test:  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses, use the following equation:


$$P = 0.6 \times I_{F(AV)} + 0.027 \times I_{F(RMS)}^2$$

For more information, please refer to the following application notes related to the power losses :


- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses on a power diode

## 1.1 Characteristics (curves)


**Figure 1. Average forward power dissipation versus average forward current**




**Figure 2. Average forward current versus ambient temperature ( $\delta = 0.5$ )**




**Figure 3. Normalized avalanche power derating versus pulse duration ( $T_j = 125$  °C)**




**Figure 4. Relative variation of thermal impedance junction to ambient versus pulse duration (SMB)**




**Figure 5. Relative variation of thermal impedance junction to lead versus pulse duration (SMB Flat)**




**Figure 6. Reverse leakage current versus reverse voltage applied (typical values)**




**Figure 7. Junction capacitance versus reverse voltage applied (typical values)**




**Figure 8. Forward voltage drop versus forward current**



**Figure 9. Thermal resistance junction to ambient versus copper surface under each lead (SMB)**



**Figure 10. Thermal resistance junction to ambient versus copper surface under each lead (SMB flat)**




## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 2.1 SMB package information

- Epoxy meets UL94, V0
- Lead-free package


**Figure 11. SMB package outline**



**Table 4. SMB package mechanical data**

| Ref. | Dimensions  |      |                             |        |
|------|-------------|------|-----------------------------|--------|
|      | Millimeters |      | Inches (for reference only) |        |
|      | Min.        | Max. | Min.                        | Max.   |
| A1   | 1.90        | 2.45 | 0.0748                      | 0.0965 |
| A2   | 0.05        | 0.20 | 0.0020                      | 0.0079 |
| b    | 1.95        | 2.20 | 0.0768                      | 0.0867 |
| c    | 0.15        | 0.40 | 0.0059                      | 0.0157 |
| D    | 3.30        | 3.95 | 0.1299                      | 0.1556 |
| E    | 5.10        | 5.60 | 0.2008                      | 0.2205 |
| E1   | 4.05        | 4.60 | 0.1594                      | 0.1811 |
| L    | 0.75        | 1.50 | 0.0295                      | 0.0591 |


**Figure 12. SMB recommended footprint**



## 2.2 SMB Flat package information

- Epoxy meets UL94, V0
- Lead-free package


**Figure 13. SMB Flat package outline**



**Table 5. SMB Flat mechanical data**

| Ref. | Dimensions  |      |      |                             |       |       |
|------|-------------|------|------|-----------------------------|-------|-------|
|      | Millimeters |      |      | Inches (for reference only) |       |       |
|      | Min.        | Typ. | Max. | Min.                        | Typ.  | Max.  |
| A    | 0.90        |      | 1.10 | 0.035                       |       | 0.043 |
| b    | 1.95        |      | 2.20 | 0.077                       |       | 0.087 |
| c    | 0.15        |      | 0.40 | 0.006                       |       | 0.016 |
| D    | 3.30        |      | 3.95 | 0.130                       |       | 0.156 |
| E    | 5.10        |      | 5.60 | 0.201                       |       | 0.220 |
| E1   | 4.05        |      | 4.60 | 0.159                       |       | 0.181 |
| L    | 0.75        |      | 1.50 | 0.030                       |       | 0.059 |
| L1   |             | 0.40 |      |                             | 0.016 |       |
| L2   |             | 0.60 |      |                             | 0.024 |       |

**Figure 14. Footprint recommendations, dimensions in mm (inches)**





### 3 Ordering information

**Table 6. Ordering information**

| Order code  | Marking | Package  | Weight  | Base qty. | Delivery mode |
|-------------|---------|----------|---------|-----------|---------------|
| STPS3H100U  | G31     | SMB      | 0.107 g | 2500      | Tape and reel |
| STPS3H100UF | FG31    | SMB Flat | 0.050 g | 5000      | Tape and reel |

## Revision history

**Table 7. Document revision history**

| Date         | Version | Changes   |
|--------------|---------|---|
| 15-Jan-2010  | 1       | First issue.  |
| 27-Sept-2018 | 2       | Updated cover page.<br>Updated <a href="#">Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)</a> .<br>Removed figure 3, figure 4, figure 5 and figure 6.<br>Minor text changes to improve readability. |
| 14-Janv-2020 | 3       | Updated <a href="#">Figure 3</a> . Minor text changes to improve readability.   |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[STPS3H100U](#) [STPS3H100UF](#)