

200V to 400VDC Input Full brick DC-DC Converters

Features

- ◆ Up to 100A Output Current
- ◆ Fast Transient Response
- ◆ Current Share
- ◆ Full Power at 85°C Baseplate
- ◆ Wide Adjustable Output Range
- ◆ Parallel Pin
- ◆ ASIC Design



Key Market Segments & Applications

- ◆ Servers & Rail Systems
- ◆ High End Computers
- ◆ Custom Power Supplies



Specifications		PAF400F280-1.8	PAF400F280-3.3	PAF400F280-5
Nominal Output Voltage	VDC	1.8	3.3	5.0
Output Current (Max)	A	100	100	80
Max Output Power	W	240	390	450
Efficiency (Typ)	%	76	83	85
Input Voltage range	VDC	200-400VDC		
Output Voltage Accuracy	%	±2		
Output Voltage Adjustment	VDC	1.0 - 2.6	2.2 - 4.2	2.9 - 6.0
Max Ripple & Noise	mV	200 (0 - 85°C)		
Max Line Regulation	mV	6	10	15
Max Load Regulation	mV	6	10	15
Temperature Coefficient	°C	0.01%/°C		
Overcurrent Protection	A	115 - 130%		
Overvoltage Protection	VDC	1.0 - 2.8	2.5 - 4.5	3.3 - 6.3
Signals & Control	-	Remote sense, remote On/Off, Parallel Pin, Inverter Good, 11-14V Auxiliary voltage		
Baseplate Temperature	°C	-20°C to +85°C Baseplate: 100% load		
Humidity (non condensing)	-	20 - 95% RH Operating, 10 - 95% RH Non Operating		
Cooling	-	Conduction (See Installation Manual for heatsink selection)		
Isolation Voltage	-	Input to Baseplate: 2500VAC (20mA); Input to Output 3000VAC (20mA) for 1 min.; Output to Baseplate: 500VDC for 1 min		
Shock	-	196.1m/s ²		
Vibration	-	Non Operating, 10-55Hz (sweep for 1 min.) Amplitude 0.825mm constant (Max 49 m/s ²) X,Y,Z 1 hour each		
Safety Agency Approvals	-	UL60950-1, CSA60950-1, EN60950-1, CE LVD		
Weight (Typ)	g	250		
Size (WxHxD)	mm	(61x12.7x116.8) See outline drawing		
Warranty	yr	2 Years		

Note: See Installation Manual for full details, test methods of parameters and application notes.

OBSOLETE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TDK-Lambda:](#)

[PAF400F280-1.8](#) [PAF400F280-3.3](#) [PAF400F280-5](#) [PAF400F2801.8](#) [PAF400F2803.3](#)