

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

2-Port DisplayPort to VGA Hub, DP1.2, TAA

MODEL NUMBER: B157-002-VGA



Converts and splits a DisplayPort video signal for display on two VGA monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms.

Description

The B157-002-VGA 2-Port DisplayPort to VGA Splitter converts and splits a DisplayPort video signal for display on two VGA-enabled monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms, this compact splitter features a built-in DisplayPort cable that connects to the source. It lets you use your existing VGA displays instead of buying new DisplayPort monitors or docking stations.

The B157-002-VGA supports video resolutions up to 1080p @ 60 Hz (1920 x 1080), as well as HDCP, EDID and DDC. Orange LEDs next to each output port indicate whether the splitter is powered on and transmitting a signal to the connected displays. The splitter works with all operating systems and is small enough to carry in your backpack or computer bag. Plug-and-play convenience means no software or drivers are needed. An included USB Micro-B cable connects between the source and the splitter to provide power, so no external power supply is required.

Features

Converts and Splits DisplayPort Signal to 2 VGA Displays SimultaneouslyIdeal for offices, conference rooms, trade shows and classroomsBuilt-in DisplayPort cable connects to sourceIncluded USB Micro-B cable supplies power to splitterSave money on new DisplayPort displays or docking stations **Top-Shelf Performance**Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)Complies with HDCP, EDID and DDCLEDs indicate whether splitter is powered on and transmitting signal to connected displays

Easy to Use Almost AnywhereWorks with all operating systemsPlug and play—no software, drivers or external power supply requiredCompact unit fits easily in backpack or computer bag

Specifications

OVERVIEW	
UPC Code	037332191496
Technology	VGA/SVGA; DisplayPort

Highlights

- Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)
- Included USB Micro-B cable supplies power to unit
- Works with all operating systems
- Compact enough for easy carrying in backpack or laptop bag
- Plug and play—no software or drivers required

Package Includes

- B157-002-VGA 2-Port
 DisplayPort to VGA Splitter
- USB Micro-B cable, 3 ft.
- Owner's manual



Max Supported Video Resolution 1080p. 68 ob Hz (1520 x 1080) Max Supported Color Depth 24-bit True Color AUDIO Audio Specification 2.0-channel surround sound audio USER INTERFACE, ALERTS & COUNCE LED Indicators (z) Orange (Monitor Signal) PHYSICAL Color Black Vire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (Inwd / In.) 1.70 x 7.90 x 5.60 Shipping Dimensions (Inwd / In.) 1.70 x 7.90 x 5.60 Shipping Weight (Ibs.) 0.60 Unit Dimensions (Inwd / In.) 1.70 x 7.90 x 5.60 Shipping Weight (Ibs.) 0.60 Unit Dimensions (Inwd / In.) 1.70 x 7.90 x 5.60 Unit Dimensions (Inwd / In.) 1.70 x 7.90 x 5.60 Shipping Weight (Ibs.) 0.60 Unit Dimensions (Inwd / In.) 1.70 x 7.42 z 2.90 Unit Dimensions (Inwd / In.) 1.54 z 2.22 s 2.00 x 2.0				
Max Supported Color Depth 24-bit True Color 3D Video Supported Yes Audio Seclification 2.0-channel surround sound audio USER INTERFACE, ALERTS & CONTROL SURROUND SU	VIDEO			
3D Video Supported Yes AUDO Audio Specification 2.0-channel surround sound audio USER INTERFACE, ALERTS & COVURATION Signal Vestore State	Max Supported Video Resolution	1080p @ 60 Hz (1920 x 1080)		
AUDIO Audio Specification 2.0-channel surround sound audio USER INTERFACE, ALERTS & CONTROLS LED Indicators (z) Orange (Monitor Signal) PHYSICAL Editation Color Black Wire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x14.22 Shipping Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Uhit Dimensions (hwd / cn) 2.55 x 6.15 x 7.6 Uhit Dimensions (hwd / mn) 2.55 x 61.5 x 7.6 Uhit Dimensions (hwd / mn) 2.55 x 61.5 x 7.6 Uhit Dimensions (hwd / mn) 2.55 x 61.5 x 7.6 Uhit Weight (bs.) 0.07 Uhit Weight (bs.) 0.154 COMMUNICATIONS EDID Compatible Yes Stde A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 Side A - Connector 1 (2) HD15 (FEMALE) Gonnector Plating Nickel	Max Supported Color Depth	24-bit True Color		
Audio Specification 2.0-channel surround sound audio USER INTERFACE, ALERTS & COURS Vol Orange (Monitor Signal) PHYSICAL Ela Indicators Color Black Wire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / cm) 1.70 x 7.90 x 5.60 Shipping Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / rm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / rm) 2.55 x 6.15 x 7.6 Unit Weight (kg) 0.07 Ox7 0.07 Computity (kg) 0.07 Outie Uniterprises (hwd / rm) 2.55 x 6.15 x 7.6 Unit Weight (bs.) 0.154 Computity (bs.) 0.154 Computity (bs.) 0.154 Connectrons Ves Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 Q (HD15 (FEMALE) Side A - Connector	3D Video Supported	Yes		
USER INTERFACE, ALERTS & CONTROLS USER INTERFACE, ALERTS & SPECIFICATIONS USER INTERFACE, ALERTS & SPECIFICATIONS USER INTERFACE, ALERTS & SPECIFICATIONS USER INTERFACE, ALERTS & CONTROLS USER INTERFACE, ALERTS & SPECIFICATIONS USER INTERFACE, ALTRES & SPECIFICATIONS USER INTERFACE, ALTRES & SPECIFICATIONS USER INTERFACE, ALTRES & SPECIFICATIONS USER INTERFACE, AND INTERFAC	AUDIO			
LED Indicators (v2) Orange (Monitor Signal) PHYSICAL Black Color Black Wire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / in.) 1.70 x 7.30 x 5.60 Shipping Veight (kg) 0.27 Shipping Veight (kg) 0.60 Unit Dimensions (hwd / in.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / in.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / in.) 0.07 Unit Dimensions (hwd / in.) 0.154 COMMUNICATIONS EDID Compatible Yes Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 Q) HD15 (FEMALE) Side B - Connector 1 Q) HD15 (FEMALE) Connector Plating Nickel	Audio Specification	2.0-channel surround sound audio		
PHYSICAL Color Black Vire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / cm) 1.70 x 7.90 x 5.60 Shipping Weight (lbs.) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m) 2.55 x 61.5 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 61.5 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 61.5 x 7.6 Unit Weight (lbs.) 0.07 Unit Weight (lbs.) 0.154 COMMUNICATIONS EDID Compatible Yes Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	USER INTERFACE, ALERTS & CON	USER INTERFACE, ALERTS & CONTROLS		
Color Black Wire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / m) 1.70 x 7.90 x 5.60 Shipping Weight (kg) 0.27 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / in.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / m) 25.5 x 6.15 x 7.6 Unit Dimensions (hwd / m) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m) 0.60 Unit Dimensions (hwd / m) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m) 0.65 Unit Dimensions (hwd / m) 0.65 Unit Weight (hg) 0.07 Unit Weight (hg) 0.07 EDIC Compatible Yes Connector S Vers Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 UNCR-USB B (FEMALE) Side B - Connector 1 Nickel <td>LED Indicators</td> <td>(x2) Orange (Monitor Signal)</td>	LED Indicators	(x2) Orange (Monitor Signal)		
Wire Gauge (AWG) 28 Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / in.) 1.70 x 7.90 x 5.60 Shipping Weight (kg) 0.27 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Weight (kg) 0.07 Unit Weight (kg) 0.07 Unit Weight (kg) 0.07 Unit Weight (bs.) 0.154 COMMUNICATIONS Yes Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 Nickel FEATURES & SPECIFICATIONS Image: SpecificationS	PHYSICAL			
Material of Construction Metal Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / in.) 1.70 x 7.90 x 5.60 Shipping Weight (kg) 0.27 Shipping Weight (bs.) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 25.5 x 6.15 x 7.6 Unit Weight (kg) 0.07 Unit Weight (kg) 0.07 Unit Weight (kg) 0.154 COMMUNICATIONS EDID Compatible Yes COMMECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Color	Black		
Shipping Dimensions (hwd / cm) 4.32 x 20.07 x 14.22 Shipping Dimensions (hwd / in.) 1.70 x 7.90 x 5.60 Shipping Weight (kg) 0.27 Shipping Weight (bs.) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / n.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / mm) 25.5 x 6.15 x 76 Unit Weight (kg) 0.07 Unit Weight (kg) 0.154 COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Wire Gauge (AWG)	28		
Shipping Dimensions (hwd / in.) 1.70 x 7.90 x 5.60 Shipping Weight (kg) 0.27 Shipping Weight (bs.) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / mm) 2.55 x 6.15 x 7.6 Unit Weight (kg) 0.07 Unit Weight (bs.) 0.154 COMMUNICATIONS EDID Compatible Yes Sconnector 1 DISPLAYPORT (MALE) Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Material of Construction	Metal		
Shipping Weight (kg) 0.27 Shipping Weight (bs.) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / in.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / mm) 25.5 x 61.5 x 7.6 Unit Weight (kg) 0.07 Unit Weight (bs.) 0.154 COMMUNICATIONS EDID Compatible Yes Ports 2 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 1 Q) HD15 (FEMALE) Side B - Connector 1 Q) HD15 (FEMALE) Side B - Connector 1 Nickel	Shipping Dimensions (hwd / cm)	4.32 x 20.07 x 14.22		
Shipping Weight (lbs.) 0.60 Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / in.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / mm) 25.5 x 61.5 x 76 Unit Weight (kg) 0.07 Unit Weight (lbs.) 0.154 COMMUNICATIONS EDID Compatible Yes Ports 2 Side A - Connector 1 Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Shipping Dimensions (hwd / in.)	1.70 x 7.90 x 5.60		
Unit Dimensions (hwd / cm) 2.55 x 6.15 x 7.6 Unit Dimensions (hwd / m.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / mm) 25.5 x 61.5 x 76 Unit Weight (kg) 0.07 Unit Weight (bs.) 0.154 COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Shipping Weight (kg)	0.27		
Unit Dimensions (hwd / in.) 1.03 x 2.42 x 2.99 Unit Dimensions (hwd / mm) 25.5 x 61.5 x 76 Unit Weight (kg) 0.07 Unit Weight (bs.) 0.154 COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Shipping Weight (lbs.)	0.60		
Unit Dimensions (hwd / mm) 25.5 x 61.5 x 76 Unit Weight (kg) 0.07 Unit Weight (lbs.) 0.154 COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 Nickel	Unit Dimensions (hwd / cm)	2.55 x 6.15 x 7.6		
Unit Weight (kg) 0.07 Unit Weight (lbs.) 0.154 COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Unit Dimensions (hwd / in.)	1.03 x 2.42 x 2.99		
Unit Weight (lbs.) 0.154 COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) DISPLAYPORT (MALE) Side B - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 Nickel	Unit Dimensions (hwd / mm)	25.5 x 61.5 x 76		
COMMUNICATIONS EDID Compatible Yes CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Unit Weight (kg)	0.07		
EDID Compatible Yes CONNECTIONS 2 Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Unit Weight (Ibs.)	0.154		
CONNECTIONS Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	COMMUNICATIONS			
Ports 2 Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	EDID Compatible	Yes		
Side A - Connector 1 DISPLAYPORT (MALE) Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	CONNECTIONS			
Side A - Connector 2 MICRO-USB B (FEMALE) Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Ports	2		
Side B - Connector 1 (2) HD15 (FEMALE) Connector Plating Nickel	Side A - Connector 1	DISPLAYPORT (MALE)		
Connector Plating Nickel FEATURES & SPECIFICATIONS	Side A - Connector 2	MICRO-USB B (FEMALE)		
FEATURES & SPECIFICATIONS	Side B - Connector 1	(2) HD15 (FEMALE)		
	Connector Plating	Nickel		
Displayport Specification 1.2	FEATURES & SPECIFICATIONS			
	Displayport Specification	1.2		



HDCP Specification	1.3	
SPECIAL FEATURES		
MST Support	No	
STANDARDS & COMPLIANCE		
Certifications	CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: B157-002-VGA