


- - 1 ASSEMBLY MAY BE BROKEN TO T
  - 2 TRUE POSITION TOLERANCE OF TH IS HELD FLAT AGAINST THE PRINT
  - THE NOTED DIMENSIONS APPLY A
  - A HOUSING: FLAME RETARDANT THEF POST: COPPER ALLOY
  - 5 FINISH: 0.000381 [.000015] GOLD OVER 0.00127 [.000050] NICKEL,



DESIRED NUM	iber (	DF PO	SITIONS		
POST TIPS AF CIRCUIT BOA		WHEN	THE HEAD	DER	
HE INTERSEC		F THE	post ani	) HOUSING	
PLASTIC; COL	OR: Bl	_ACK.			
N CONTACT / NTIRE POST.	REA,				
		0.06			
101.1 [3.98] 98.6	$\frac{9}{4}$	900 <u>900</u> 552	] 39	80	4-146495-0
98.65 [3.88] _96.1		5.52 800 3.98	38	78	3-146495-9
[3.78 93.5 [3.68	4][3.	700	37	76	3-146495-8
[ <u>3.68</u> 91.0 [3.58		1.44 600 <u></u> 3.90 500	36 35	74	3-146495-7 3-146495-6
<u>[3.58</u> 88.49 [3.48]		<u>500</u> 6.36 400	33 34	72	3-146495-5
<u>_3.48</u> 85.99 [3.38		<u>400</u> 3.82 300	33	68	3-146495-4
<u> </u>		<u>300</u> 1.28 200	32	66	3-146495-3
80.8 80.8	7 78	<u>200</u> 3.74 <sub>-</sub> 100	31	64	3-146495-2
	+ <u>]</u> [ <u></u> ]. 3   7( 4][_3	<u> </u>	30	62	3-146495-1
 	$\overline{\boldsymbol{\beta}}$	<u>3.66</u> 900	29	60	3-146495-0
73.28 [2.88	5 - 7'	1.12 800	28	58	2-146495-9
 [2.78	1_68	B.58 700	27	56	2-146495-8
_ 68.1 [2.68	7 60 4][2.	5.04 600	] 26	54	2-146495-7
65.60 [2.58	4∥2.	3.50 500	] 25	52	2-146495-6
63.09		).96 400	] 24	50	2-146495-5
60.55			] 23	48	2-146495-4
58.0	4」[2.	5.88	] 22	46	2-146495-3
55.4	4」[2.	3.34	21	44	2-146495-2
52.9 [2.08 _50.3	4」[2.	0.80	] 20	42	2-146495-1
[1.98]		B.26 900 5.72	] 19	40	2-146495-0
[1.88]	4」[1.	<u>800</u> 3.18_	18	38	1-146495-9
[1.78]	4 <u> </u> 1.	700 <u></u> 0.64	17	36	1-146495-8
1.68	4][1. 3_  38	<u>600</u> 3.10	16	34	1-146495-7
1.58	4][1. 935	<u>500</u> 5.56	15	32	1-146495-6
<u>1.48</u> <u>35.1</u>	53	<u>400</u> 3,02 -	13	28	1-146495-4
[1.38 32.6 [1.28		<u>300</u> ).48_	12	26	1-146495-3
_ 30.0	7 _ 27	<u>200</u> 7.94 -		24	1-146495-2
<u> </u>	325	<u>100</u> 5.40 000	10	22	1-146495-1
24.99	922	2.86 200]	9	20	1-146495-0
22.4	52(	).32 300]	8	18	146495-9
19.9	$\frac{1}{1}$ $\frac{1}{1}$	7.78 700]	7	16	146495-8
17.3	71 5	5.24 500]	6	14	146495-7
14.8			5	12	146495-6
12.29	9 10 -][.4	).16 400]	4	10	146495-5
9.75		.62 300]	3	8	146495-4
7.2	F][.2	.08 200]	2	6	146495-3
4.67	-][.2	.54 100]	1	4	146495-2
2.13 [.084	]	_	_	2	146495-1
G		<b>—</b>		NO. OF POSITIONS	PART NUMBER
ROLLED DOCUMENT.	СНК		12/5/95 1/2/96	S TE	TE Connectivity
TOLERANCES UNLESS DTHERWISE SPECIFIED:	G. DUE APVD G. DUE PRODUCT SP		1/2/96 NAME	header asse	EMBLY, MOD II,
.C ± _					DOUBLE ROW, T, UNSHROUDED

D

1

ں

А

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 2-146495-0